## UNCLASSIFIED AD/42069

## Armed Services Technical Information Agency

ARLINGTON HALL STATION ARLINGTON 12 VIRGINIA

FOR

MICRO-CARD

CONTROL ONLY

NOTICE: WHEN GOVERNMENT OR OTHER DRAWINGS, SPECIFICATIONS OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE U.S. GOVERNMENT THEREBY INCURS NO RESPONSIBILITY, NOR ANY OBLIGATION WHATSOEVER; AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS, OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE USE OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERESO

UNCLASSIFIED

WAIN: TRCHNICAL REPORT 55-160
PART 5
ARTIA INCUMENT No. AD 142009

(121)

### MATERIALS-PROPERTY-DESIGN CRITERIA FOR METALS

PAPT 5. THE CONVENTIONAL SHORT-TIME, ELEVATED-TEMPERATURE PROPERTIES OF SELECTED STAINLESS STEELS AND SUPER ALLOYS

RONALD J. FAVOR
PILLIAM P. ACHBACH
WALTER S. HYLER

BATTELLE MEMORIAL INSTITUTE

OCTOBER 1957

This report is not to be announced or distributed automatically in accordance with AFR 205-43A, paragraph 6d.

WRIGHT AIR DEVELOPMENT CENTER

## BEST

# AVAILABLE

COPY

WADC TECHNICAL REPORT 55-150 PART 5 ASTIA DOCUMENT NO. AD 142069

#### MATERIALS-PROPERTY-DESIGN CRITERIA FOR METALS

PART 5. THE CONVENTIONAL SHORT-TIME, ELEVATED-TEMPERATURE PROPERTIES OF SELECTED STAINLESS STEELS AND SUPER ALLOYS

RONALD J. FAVOR WILLIAM P. ACHBACH WALTER S. HYLER

BATTELLE MEMORIAL INSTITUTE

OCTOBER 1937

MATERIALS LABORATORY
CONTRACT No. AF 33(616)-2303
PROJECT No. 7360

WRIGHT AIR DEVELOPMENT CENTER
AIR RESEARCH AND DEVELOPMENT COMMAND
UNITED STATES AIR FORCE
WRIGHT-PATTERSON AIR FORCE BASE. OHIO

Organise Lathorn Pring Co., Spreighold, O. 418: - Lincomber 1957

#### PORTYCKO

This report was prepared by Bettelle Memorial Institute, Columbus, Ohio, under Contract No. AF 33(616)-2303. The investigation was initiated under Project No. 7360, "Materials Analysis and Evaluation Techniques", Task No. 73605, "Design Data for Metals". It was administered under the direction of the Meterials Inboratory, Directorate of Emboratories, Wright Air Development Center with Nr. D. A. Shinn setting as project engineer.

This research has been earried out under the supervision of H. J. Grover, Chief of the Applied Mechanics Division, with considerable valuable consultation from S. A. Gordon. Other Bettelle staff members who participated to a considerable extent in the progress include A. H. Hunter, N. J. Weller, W. L. Belton, and I. E. Hanna.

This report covers work conducted from January 1, 1956, to Escenber 15, 1956.

WADC TR 55-150 Pt 5

#### ABSTRACT

Presented in this report is a compilation of data on the conventional short-time, elevated-temperature properties of selected corrosion-resistant and high-temperature alloys applicable to airframe and missile fabrication. The resultant recommended design data obtained in this study have been presented in such form as to be directly applicable to the ANC-5 Bulletin (issued by the Air Force-Navy-Civil Panel) on "Strength of Metal Aircraft Elements".

#### PUBLICATION REVIEW

This report has been reviewed and is approved,

FOR THE COMMANDER:

REKUNNEST

R. R. KERNEDY Chief Metals Branch Materials Laboratory

WADC TR 55-150 Pt 5

iii

#### TABLE OF CONTENTS

<u> </u>	7.
Brimodection	4
NETHOD OF APPROACH.	3
General Companies,	3
Treatment of Strength Properties For Frys Fers Face Florer and Florer and Florer	4
Data Fram One Secret	4
Dum From Mare Than Cor Scarce	4
(Fg)	4
Free Feys right Phen and Fhey) and a complete and a	•
Trestment of Modulus of Electricity (E and Ec) and Stress-Strain Data (Optimization Process) ,	•
General	5
Machemetr's Details of Optimiselies of Modules Data	
	11
STAINLESS STEEL	<b>41</b>
	<b>6</b> 6
AM . 354 STADQLESS STEEL	N.
17- PM STADQESS STEEL	14
19-90; ALLOY (AMS-5504) (AMS-5504)	14
19- 10X ALLOT (AMS-5539)	<b>&gt;</b> 1
A-296 ALLOY	<b>24</b>
DICURCEL TX* (MIEL-IS-2786)(AMS-SS4RL)	t <del>y</del>
STAINLESS THE ALLOY	h
APPENDIX I, HATERIAL COMPARISON CURVES	<b>.</b> \$
APPENDIX II, LIST OF RETELLENCES	73
LIST OF TABLES	
Table 1. Nessand Christical Composition of A251 301 State*er's Sq. of (NO-S-692, FS 361)	11
Table 2. Kummum Acpresentative Mechanical Properties Wifel 191 Stanless Sheet (QQ-S-642, FS 201)	1.1
Table 3. Hemani Chemical Composition of 422M Stainburn Steel	7
Table 4. Named Chemical Composition of 17-7PH Stamless Steel (AMS-5527)	13
Teble 2. Minimum Mechanical Properties of 17-7PH Stamicas Steel (AMS-5529).	La
Table 6. Honoral Christian Countesting of AM-350 Standers Speak.	<b>12</b>
Table 7. Homani Chromoni Corsposition of 17-47ti Standens Seed	<b>'</b>
Table R. Typical Chemical Correction of 19-70L Bros-Browniant Alloy (AMS-5526B) (AMS-5527A)	4
Table 9. Mitamuse Perchanical Properties of 19-10L-Alloy (AMS-55248)	<b>14</b>
Table 16. Missaury Mertense al Propyrises of 19-90L Albry (AMS-9527h)	17
Table 21. Typical Christical Composition of 19-9DX Heat-Res	<b>H</b>
Table 12. Minimum Mechanical Properties of 19-90X Alloy (AMS-553M)	•
may the saulte has a	

#### LET OF TABLES

		km.
	distinum Methanical Properties of 19-90% Alley (AMS-9539)	***
	Typical Chemical Composition of A-200 Alloy	114
Table 15, C	Demical Composition of Incomet "X" (MILLIN-7786) (AMS-55425)	119
Table 14, T	Spical Room-Temperatore Properties of Forty Heat-Treated Hat-Rolled Income one	410
Table 17. 1	spical Roote-Temperature Properties of Hat-Rolled and Aged Income of water and the second of the sec	114
	diaimum Mechanical Properties of Income! "X" (AMS-5542D)	414
	feminal Chemical Composition of Stamless WW Alloy	14
	LBT OF ILLUSTRATIONS	•
Pigure 1.	Tennile Modulus Versus Temperature for 2014-T6 Clad Alexandra Alley	
Figure 2	Canaile Modules Versus Temperature for 2026-781 Aluminum Alley	•
igure 3.	Schematic Diagram of Quantities Described in Optimization Process	•
Figure 4	Tensile Strength (Ign) of alSt 201 (Half Hard) Staniesa Steel at Elevated Temperature	10
•	•	**
Figire 4,	Effect of Strain Raie on the Tennile Strength (Fp.) of AlSI 301 (Half Rard) Standard Standard at Elevel 4 Temperature	14
Eigare 6,	Tennile Strength (Fee) Empressed as a Percentage of Room-Temperature Tennile Strength of A151 301 (Half Hord) Stataless Stret of Elevated Temperature	16
Figure 7,	Design Curve for Tennile Strength (Ftm) of AISI 301 (Half Hard) Strinlers Store at Elevated Temperature	16
Figure A.	Conside Field Strength (Fry) of AISI 361 (Half Hard) Stamless Stret at Electric Temperature	11
Figure 9.	Effect of Strain Rate on the Travile Tield Screegth (Fey) of AISI 301 (Molf Bord) Securious Bood at Elevated Lemperature	14
Figure 10,	Tennile Yield Strength (Ftyl of AISI 301 (Half Hard) Stainless Scotl at Envand 1	19
Figure 11.	Design Curve for Tenatic Title Strength (Fay) of AISI 301 (Half Hard) Stainbess Stant at Elevated Temperature	•
Figure 12,	Commessive Vield Strength (For Expressed as Percentage of Room Temperature Compensator	14
	Tield St. ength of Att 301 (Half Hard) Stainless Steel at Elevated Temperature	#1
Figure 13,	Design Curve for Compressive Tield Strength (Fey) of AISI No. (Half Bard) Semiles Start of Elevated Temperature	21
Figure 14,	Bearing Strength (Phra) of AISL 361 (Roll Hard) Stainless Swel at Elevated Temperature	40
Figure 15,	Bearing Strength (Fhru) Expressed as a Percentage of Room-Temperature Bearing Strength of AISI 301 (Half Hard) Stataless Strel at Elevated Temperature	14
Figure 16,	Design Curve for Bearing Strength (Form) of ASS 201 (Half sland) Statutes Stand at Elevated Temperature	24
Figure 17,	Bearing Tield Strength (Fhry) of ASS 301 (Half Hard) Stamless Steel at Elevated Tataparathen	36
Figure 18,	Bearing Yield Strongth (Fbry) Expressed as a Percentage of Recon-Temperature Bec-no Todd Stre., 3th of Al51 301 "Init Hard) Stamicus Steel of Elevand Temperature	,

MAC 72 35-450 PL 5

and the second of the second of the second

#### (Continued)

France 17	Drage Curve for Process Treet Surveyes (F <sub>bey</sub> ) of AISI 301 (Hot! Nord) Standess Steel at Elevated Temperature	24
F-f 24	Second from the second of the Control	29
Figure 21	. Drage Curve for Sheer Strongth (Fm) of ASS 101 (Mail Hard) Stainless Steel at Elevated Temperature	30
Figure 22	. Transle Mattains (E) of A.25, 194 (Mail Mart) Stataless Steel at Elevand Temperature	21
Papers 23	. Touside Stress-Strain Corvo det AIS 911 (Half hard) Stainless Seel at Room Temperature	N
Name of	Tousile Stress-Straze Carmes for A.S.; 361 (Half Hard) Stainless Steel at 400 F,,,	33
Adeta 50	Effect of Strain Rain on the Transit Strans-Strain Curve of AISI 301 (Half Hard) Stambers Stock of 460 F	H
clar :s	Treasile Stress-Stress Carves but ASS M1 (Half Hard) Stataless Strel at 680 F	31
Figure 27.	Touaile Stress-Steam Carves for ASC M4 (Half Hard) Stainless Steel at 600 F	34
Page 28	Toualdo Brosa-Arain Curves for A.S.: 191 (Half Harr) Stainless Reel at 1866 F	37
Pageire 49.	Touside Arres-Stram Curves the 3 % Mil (Half Hard) Signalous Stret on 1246 F	34
Land in	Compressive Madatus ( $\Sigma_c$ ) or AEC N1 (BAH Hard) Stainless Steel at Elevated Temperature	39
Figure 31.	Compressive Street-Street Corne for ASC 344 (Half Hard) Stanless Strel at Room Temperature .	44
Figure 32.	Compressive Stream-Stream Curves for AZS: 361 (Half Hard) Stamless Steel at 400 F	41
Figure 33.	Compressive Stress-Stress Corves for AIS: 341 (Half Hard) Stataless Steel at 600 F	42
Figure 34.	Compressive Stress-Stress Oscors for ASS 301 (Hell Hard) Stamless Steel at 300 F	43
Pages 14	Compressive Streen-Streen Ourses ter ASS 341 (Half Hard) Stataless Street at 1600 F	44
Figure 56.	Founds Strength (Fre) of ASS: We (Feel Mare) Standers Steel at Elevated Temperature	45
Figure 17,	Effect of Stra. 2 Hair on the Tonneir Strength (F <sub>ER</sub> ) of ASS 301 (Full Hard) Standens Stand at Elevated Temperature	44
Figure M.	Trustle Strength (T <sub>fe</sub> ) Expressed as a Percentage of Room-Temperature Tourile Strength of ASS 981 (Full Mars) Stammes Seed at Elevated Temperature	47
Figur 1A	Drage Curve for Teamle Strong (Pos) of AISL 101 (Post Hard) Standard Stool at Elevated Temperature	44
Topare 44.	Treasure Tirest Strongen (Fre) of ASS 301 (Fall Hard) Stateboor Steel at Exercised Temperature	.19
Fyar 41.	Effect of Arosa Base on the Tunnin Foots Strongth (Fig) of AISI 301 (Fall Mari) Sumbon Avel of Biomand Temperature	•
Figure 4.	Druge Curw for Trends Treis Strongth (V <sub>17</sub> ) of ASS 561 (Tall Hard) Sambon Such at Elevated Temperature	<b>5</b> 1
Carry 45	Descript Strong to F. J. of 622M Standings Store at Elevated Temperature	*3

#### LIST OF ILLUSTRATIONS (Continued)

		-3
Flavre 66	6. Draign Curve for Tensile Birength (Fig.) of 422M State, san Stool at Elevated Temporature 💎 👡 👡	. 34
Figure 49	s. Tensile Yield Strangth (F <sub>ty</sub> ) of 422M Stainless Steel at Elevated Temperature	. 34
Figure 44	). Design Curve for Tensile Vield Strongth (F <sub>ty</sub> ) of 422M Stataless Seed at Elevated Temperature	34
Figure 47	r. Tenuite Stress-Strain Curves for 42?M Stainlean Steel at Room Temperature	97
Figure 48	). Tensile Stress-Strain Curve for 41:1M Statillese Steel at Room Temperature	39
Figure 49	). Tonaile Strass-Strain Curve for 44255 Stainless Strei et Room Temperature	70
Figure 50	). Tensile Stress-Strain Curve for 41M Stainless Steel at Room Temperature	44
Figure 51	. Tousile Strees-Strain Curves for 421M Stanless Steel at Room Temperature	u
Figure 12	Tensile Stress-Stress Curves for 423M Stainless Sicel at Room Temperature	u
Figure 55	. Tenatla Stress-Strain Curves for 422M Stainless Siesl at Room Temporature	43
Frgore 54.	. Tensile Stress-Strein Curve for 422M Stainless Steel at Room Temperature	44
Figure 55.	, Tensile Stress-Strain Curves for 422M Stainless Steel at Room Temperature	45
Elgure \$4.	. Tenuile Stress-Strain Curves for 622M Stainless Steel at Room Temperature	44
Figure 51.	Tensile Striss-Strain Curve for 422M Stainless Steel at Room Temperature	67
Figure 58.	Tensite Strength (Few) of 17-7PH (TH 1040) Stainless Steel of Elevated Temperature	70
Figure 59.	Effect of Strain Rate or the Tensile Strength (F <sub>tu</sub> ) of 17-7PF (TH 1850) Stav.ioco Steat at Elevated Temperature	31
Figure 60,	Design Gyrve for Tensile Strongth (Fig.) of 17-7PH (TN 1048) Stainless Steel at Elevated Temperature	72
Figure 61.	Tensile Yield Strangth (Fty) of 17-7PH (TH 1850) Stainless Seel at Elevated Temperature	13
Figure 42,	Effect of Strain Rate on the Tensile Yield Strongth (Fty) of 17-7PH (TH 1050) Stainless Suel of Elevated Temperature	*
Figure 61.	Design Curve for Feneric Yield Strength (Fig.) of 17-7PM (TN 1050) Stainless Streit at 5 tevated Temperature	75
Figure 64,	Compressive Yield Strength (Fcy) of 17-7PH (TH 1050) Statuless Steel at Elevated Temperature	*
Figure 65,	Design Curve for Compressive Yield Strength (F <sub>CY</sub> ) of 17-7PH (TH 1050) Statuless Steel at Elevated Temperature	11
Figure 66	Bearing Strength (Faru) of 17-7PH (TH 1050) Stainless Steel at Elevated Temperature	76
Fågure 61.	Design Curve for Bearing Scrength (Fare) of 17-7PH (TH 1050) Stainless Seel at Elemeted Temperature	71
Figure 60.	Rearing Ticlé Strength (Fpry) of 17-7PH (TH 1959) Stauness Seel at Elevated Temperature	-
	Design Curve for Bearing Yield Strength (F <sub>BPY</sub> ) of 17-7PH (TH 1650) Standens Shoot at Sleveled Temperature	

MADE TO 55-450 24 5

#### (Comment)

		Page
Eugene 78.	Shear Strength (Fox) of 17-1798 (IN 1056) Stateleys Stept as birroard Temperature	₩.
Fgwr H.	Drogs Corve for Series Strongth (Fpm) of 17-7PH (TH 1994) Nambors Steel at Elevated Temperature	03
Figure 12.	Treatis Sendales (Eg et 17-799 (TM 1252) Standers Strei at Envated Temperature	•
Fagur 73.	Treache Stress-Stram Carry for 17-TPp* (TH 1050) Stateless Seel of Reser Temperomee	<b>0</b> 5
Fagure 14.	Jenacle Stress-Stress Corves for 17-7PH (TH 1050) Blainless Strett at 460 F	*4
Figure 74,	Tensuir Stress-Scrout Curves for 17-7PH (TH 1050) Mainless Street at 600 F	87
Figure 76.	Tensoir Stress-Stram Corms for 17-7PH (TH 1650) Staintess Steel at 660 F	14
Fagure 77,	Tempolie Stress-Stress Corve for 17-TPH (TH 1050) Stainless Meet at 900 F	n
Figure 78.	Compare neave Madalar (Eq.) of 17-7PH (TH 1050) Stainless Blood at Elevated Tempera, as	76
Figure 79.	Compressive Stress-Stress Carve for 17-7PH (TH 1050) Mainless Seel at Room Temperature	91
Figure 64,	Compressive Stress-Stress Carross for 17-7PH (TH 1650) Intainless Sheet at 480 F	92
Espare 61.	Comper sour Mrrad-Stram Carves for 17-7PH (TH 1050) Mainleas Steel at 440 F	93
Fagure &L	Compression Screne-Stress Curve for 47-7PH (TH 1054) Meinless Sheet at 886 1:	94
Figure 4).	Compressive Streen-Streen Curves for 17-7PH (TH 1050) 41 940 8"	15
Figure 84.	Comparessive Modulus (Eq.) of 17-7PH Stamless Steri at Kievaled Tomperature	76
Figure 85.	Compressive Stress-Stress Corves for 17-7PH Stainless (Root of Boom and Element Temperature .	47
Figure 64.	Troube Strength (F.,) of 17-TPH (TH 950) Stamless Steel & Floro vol. Temperature	78
Eigure 27,	Design Curve for Tennale Strength (Fig.) of 17-TPH (TH 450) Maintens Steel at Elevated Temperature	**
Figure M.	Tennie Tield Strongth (Fry.) of 17-7PH of (TH 950) Stainless Stool of Elevated Temp-reture	190
Fagure III.	Design Carve for Tendale Field Strength (Fty.) of 17-7PH (\$14.954) Standard Stort at Excepted Temperature	101
Figure 99,	Transc Strength (Fm) of AM-350 Structus Stret (Solution Host Treated at 1780 F) at Elevated Temperature	104
Figure 91,	Design Curve for Tenocic Strength ( $F_{to}$ ) of AM-350 Stainless (not)   Solution Heat Trusted at 1700 F) at Elevated Temperature $-$ ,	1 05
Figvst N.	Teamle Tork Strength (7cg) ANd Standers Steel (Salution Heat Treated at 1700 F)  Elevated Temperature	106
Figure 93,	Desire Curve for Tennic Yield Strength (F <sub>1y</sub> ) of AM-310 Bigintons Short (Salution Heat Treated or 1700 7) at Elevated Temperature	107
Figure 91.	Trancle Modulus (ET of AM-Y56 Skamless Sine: (Solution Nest Transc at 1700 F) at Elemand Temperature	. 00
Figure 95.	Tenacie Strength (F <sub>CD</sub> ) of A3350 Strendens Stret (Solution Hoot Transled at 1740 F) at Elemand Temperature	109

PARK IN 55-250 IN 5

#### LIST OF ILLUSTRATIONS (Comment)

	·	Pas
Pigure %.	Design Curve for Tennile Strength (Ftm) of AM-350 Stainless Stret (Solution Heat Trented at 1750 F) at Elevated Temperature	110
Espare Vi.	Tenail: Tield Strength $\{F_{ij}\}$ of AM-350 Scalaless Steel (Solution Heat Treated at 1750 F) at Elemind Temperature	ш
figure %.	Design Cirve for Tensile Yield Strength (Fty) of AM 350 Stainless Steel (Solution Heat Treated as 1750 F) at Elevated Temperature	117
Figure 99.	Tensile Modulus (E) of AM-350 Stainless Steet (Solution Heat Treated at 1750 F) at Elevated Temperature	113
Figure 100,	Tennile Strength (Fig.) of AM-350 Stamless Stee! (Double Aged) at Elevated Temperature	114
Figure 191,	De sign Carve for Tentile Strength (Few) of AM-350 Stataless Steel (Double Aged) at Elevated Temperature	115
Figure 182,	Tensile Tield Strength (Fty) of AM-350 Stainles: Sicel (Double Aged) at Elevated Temperature	116
Figure 181	Design Curve for Tensile Yield Strength (Fty) of Ani-150 Stainless Steel (Double Aged) at Elevated Temperature	117
Figure 194,	Tensile Modulus (E) of AM-350 Stantices Steel (Double Aged) at Elevated Temperature	110
Figure 105,	Shear Strength ( $F_{00}$ ) of AM-350 Stamess Steel at Elevated Temperature	11.3
Figure 184	Design Carve for Shear Strength (Fam) of Ald-350 Stainless Steel at Elevated Temperature	150
Figure 107,	Compressive Tield Strength ( $F_{Cy}$ ) of AM-350 Stainless Steel at Elevated Temperature	(5)
Figure 100.	Design Curve for Compressive Tield Str. agth (F <sub>c.y.</sub> ) of AM-350 Stainless Steel at Elevated Temperature	124
fyze 10.	Tennile Modulus (E) of AM-350 Stamless Steel at Elevated Temperature	153
Figure 118,	Tensule Stre - Strain Curves for AM-350 Stainless Steel at Room Temperature	124
Page - 111,	Tennile Stress-Strain Curves for AM-350 Stainless Steel at Room and Elevated Temperature	125
Figure 112,	Compressive Modulus (Ec) of AM-350 St. inless Steel at Klevsted Temperature	176
Figure 415.	Compressive Stress-Strain Curves for AM-350 Stainless Steel of Room ast.  Elevated Temperature	127
Figure 110.	Effect of Annealing at 1700 F and 1750 F on the Tennile Stress-Strain Curve of AM-350 Stamless Steel at Room Temperature ( Langitudinal Property)	128
Dgure 115,	Eilect of Annealing at 1700 F, 1750 F, and 1900 F, on the Tensile Stress-Strain Curve of AM-350 Stainless Steel at Room Temperature (Transverse Property)	129
Figure *14,	Effect of Annealing at 1700 F, 1758 F, 1800 F, and 1900 F, Subsero Cooling, and Tempering on the Temple Stress-Strain Curve of AM-350 Stauless Seel at Room Temperature (Longitudina) Property)	130
Figure 117,	Effect of Annualing, Subsero Cooling, and Tempering on the Tennile Stress-Stress Cerve of AM-350 Stainless Steel at Room Temperature (Transverse Property)	131
Figure 116,	alffect of Annealing at 1700 F, 1750 F, 1800 F, and 1900 F. Air Cooling, and Double Aging on the Teorile Circus-Strein Curve of Abt-150 features, Streigt Room Temperature (Longitudina) Property)	132

mar 100 55-150 300 5


#### LIST OF ILLUSTRATIONS (Continues)

		Page
Figure 119.	Effect of Assesting at 1700 F, 1750 F, and 1900 F. Air Cooling, and Double Aging on the Tension Stress-Stress Curve of AM-350 Statuless Meet at Room Temperature (Transverse Property)	133
	·	
	Effect or Assessing at 1700 F on the Compressive Stress-Stram Corre of AM-350 Stainless Steel at From Temperature (Longitudian) Property)	134
Fig. 171.	Effect of Annealing at 1700 F on the Compressive Stress-Stram Course of AM-150 Strinless Steel at Room Temperature (Transverse Property)	135
Figure ILL.	Effect of Anaraling, Subsero Cooling, and Tempering on the Compressive Stress-Strain Curve of AM-150 Stainless Steel at Room Temperature (Longited and Property)	134
Fagure 125	Ethers of America, Subserv Choling, and Tempering on the Compressive Stress-Strain Curve of AM-150 Stainless Steel at Room Temperature (Transverse Property)	137
Figure 124.	Effect of Anneeling at 1700 F and 1750 F and Standard Donber Aging on the Compressive F reno- Strain Curve of AM-150 Stainless Steel at Room Temperature (Longitudinal Property)	138
Expere 125.	Effect of Annealing at 1700 l' and 1750 F and Standard Dowler Aging on the Compressive Stress-Strain Carve of Akt-150 Stainless Strel at Room Temperature (Transverse Property)	134
Figure 126.	Tenasio Strength (Fig) of 17-479 Stateless Steel at Elevated Temperature	141
_	$Perigs$ Curve for Teasile Strength ( $F_{Lo}$ ) of 17-4PH Stansiess Steel at Elevated Temperature	142
	Tenable Torid Strongth ( $F_{xy}$ ) of 17-4PH Storoler's Steel at Elevated Temperature	143
Figure 123.	Design Carve for Teasile Tield Strength (Fig.) of 17-4PH Stamless Steri at Elevated Temperature	141
Figure 13C.	Compressive and Strength ( $F_{CT}$ ) of 17-4PN Huminess Steel at Elevated Temperature	145
-	Design Curve for Compressive Yield Strength ( $F_{cg}$ ) of 17-4FH Standess Steel at Eigenand Temperature ,	144
	Shear Strength (Foul) of 27-4PH Stataless Steel at Elevated Temperature	147
	Orsign Carve for Sheer Strength (F 12) of 17-4PH Stamless Steel at Elevated Temperature	148
	Bearing Strength (Farm) of 17-6PH Stainless Steel at Elevated Temperature	149
-	Design Carve for Beating Strength (Figure of 17-4PH Statishess Steel at Elevated Temperature	150
	Bearing Toold Strength (F <sub>bey</sub> ) of 17-4PH Stauless Steel at Elevated Temperature	151
	Drugs Unive for Bearing Yield Strength (Fury) of 17-4PH Stainless Stort at Elevated Temperature	152
-	Effect of Exposure 1 Elevated Temperature on the Room-Temperature Tensile Strength (Fpg) of 17-4PE Stainless Steel	153
=	Tennile Medulus (E) of 17-4PH Stainless Steel Forging or Executed Temperature	154
•	Trunia Stress-Strain Curves for 17-4PH Stainless Stort Forging at Room Temperature and Elevated Tomperature	155
Figure 141.	Compressive Modules ( $K_c$ ) of 17-4PH Stainless Steel Forging at Elevated Temperature	196

BADC TRUS-150 PG

#### LIST OF ILLUSTRATIONS (Continues)

		ם
Figure 142.	Compressive Stress-Stram Carves for 17-4PH Stainles Str. 1 Forging at Room and Elevated Tempera mee	157
Figure 143,	Temple Strength (Fm) of 19-9DL Stainless Steel (Annealed) at Elevated Temperature	169
Figure 144.	Design Carve for Yeasile Strength (Fig.) of 19-9DL Stateles, Steel (Annualed) at Rievated Temperature	161
rigure 145.	Tensile Tield Strength (Fig.) of 19-vDL Stainless Steel (Anaroled) at Elevated Temperature	142
Figure 144.	Design Corve for Tousile Tield Strength (Fty) of 19-9DL Stainless Stret (Annualed) at Lieunted Temperature	165
Figure 147.	Tensile Strength (Fgg) of 19-9DL Stainless Steel (Cold Rolled) at Elevated Temperature	164
Figure 14A.	De un Cares for Tenotic Strongth (Fig.) of 19-9DL Stataless Steel (Cold h'allod) at Lievated Temperature	145
Figure 149.	Tensile Tmil Struggta (Fry) of 19-9DL Stataless Steel (Cold Rolled) at Elevited Temperature	166
Figure 150,	Design Curve for Turbile Tield Strength (Fty) of 19-9DL Stainless Steel (Colc Relied) at Elevated Temperature	167
Figure 151,	Tennile Strength (Fra) of 19-9DL Stateless Steel (Hot Rolled and Strens Relieval) at Elevated Temperature	168
Figure 152,	Design Carw for Tennile Strongth (Fig.) of 19-9DL Stainless Steel (Not Rolled and Stress Rallevel) as Elevated Temperature	149
l'igure 153.	Teamle Tield Strength (F., ) of 19-10L Stainless Steel (Hot Rolled and Strens Relieved) at Elevated Temperature	170
Flegus 154,	Design Curve for Tenaile Tield Strength (Fty) of 19-9DL Stainless Sicel (Hot Rolles and Strees Relieved) at Elevated Temperature	171
<b>Tg</b> ure 155,	Tennile Strength (Fm) of 19-4DL Stainless Steel (Ho' Forged) at Elevated Temperature	178
F <b>g</b> ure 156.	Design Curve for Teasile Strength (Fig.) of 19-9DL Stataless Steel (Hot Forgod) at Elevated Temperature	173
figure 157.	Tennile Strength (Fg.) of 19-9DL Stainless Steel (Hot Kolled) at Elevated Temperature	174
Fagure 158,	Design Carve for Teasile Strengta (Fig.) of 19-9DL Statalnes Steel (Not Railed) at Elevated Temperature	175
Fagure 159.	Tensile Swength (F ca) of 19-9DL Strinices Steel (Hot Rolled) at Elevated Temperature	176
Figure 160,	Design Curve for Tennile Strength (Fig.) of 19-9DL Steinless Steel (Not Rolled) at Elevaned Temperature	177
Figure 161.	Tensile field Strength ( $F_{Sy}$ ) of 19-9DL Stainless Steel (Hot Rolled) at Elevated Temperature	170
figure 162.	Design Come for Tounds Yield Strength (Fty) of 19-9DL Stainless Steel (Not Rolled) at Elevated Temperature	179
Tagure 163.	Tensile Strength ( $F_{EH}$ ) of 19-9DL Stainless Steel (Forging) at Elevated Temperature	100
Figure 164.	Design Curve for Tennile Strength (Fru) of 19-9DL Statules: Size! (Forgon) at Figure 19-9DL Statules: Size!	101



NADC TESSIN PO

#### (Contrart)

			<u></u>	Ľ
Figure 165.	Tensile Torid Strengths ( $F_{Ty}$ ) of 19-9DL Stainless Seel (Forgog) at Ebessied Temperature , ,	•	10	Ŋ
Figure 166.	Design Curve for Teas in Yout Strength (Fig.) of 19-9DL manners aren's Forgong. at Element Temperature	-	11	ı 🅦
Figure 167,	Tourise Strongth ( $F_{\rm mp}$ ) of 19-4Di, Standous Strel (Hot Robot) on Edward Temperature	•	10	H
Figure 168.	Design Carrie for Transle Strengts (Fig.) of 19-9DL Stainless Speci (N. Ralled) at Elevated Temperature	•	10	5
Frence 169.	Trivile Tierd Strengtz (Fyg) of 19-9DL Stainless Steel (N.A Rochel) of Lorented Temperature	-	14	
Figure 170.	Design Carm for Yearin Lield Strongth (Fig.) of 19-9DL Standors Soci-(Flat Racies) of Elevated Temperature	•	16	.7
Fagure 171.	Termin Serveges, $F_{\rm Em}$ ) of 19-40% Standard Stee. (For-Code Warbed) at Element Temperature .	•	4.	4
F 14 . er 172.	Design Carse for Texaus Strongth (Fig.) of 19-9DL Stainless Seed (Hot-Cold Verbed). a: Esevated Temperature	•	10	19
Figure 173.	Tensile Strong- $\{f_{nn}\} \subset \mathbb{N}^{-4}$ DL Statutess Steel (Hot-Cold V around) of Element Temperature .	-	17	•
Figure 174.	Design Curve for Tensile Strengtz (Fig.) of 10-9DL Stainless Strel (Not-Cold Worked) at Elevated Temperature	-	19	NI.
F.4me 175.	Tensile Treid Sweigen (Fyy) of 19-90L Rainless Steel (Hot Rolled) at Cornard Temperature		17	ę
Fagure 176.	Draigs Carw for Tenade Yacid Strength (Fgy) of 19-904. Standens Lovel (Not Halland) at Elevates Temperature	-	19	3
Fagrice 177,	Tens sie Strength (Fres) of 19-60X (AMS-55M) Stataless Seetl at Elevated Temperament	•	1.	•
Figure 174,	Texatle Strength (Fm) of 19-92X (AMS-5534) Statuless Seed at Elemant Temperature	•	19	7
Figure 179,	Design Carrie for Tennile Strength (F <sub>Fe</sub> ) of 19-10X (AMS-5538) Stonders Sinci at Elevated Temperature	•	19	•
Figure 160,	Tousile Tield Strength (F $_{\overline{1}\overline{2}}$ ) of 19.00X (A325-5525) diameters Streif at Elevated Temperature $_{-}$ ,	•	19	7
è igure 18',	Transic Torid Strength (Fig.) Expressed as a Percentage of Room-Temperature Temple Yield Strength of 15-90% (AMS:5530) Manueso Steel at Elevated Temperature	•	20	•
Figure 162,	Drigo Curve for Tenaue Yield Strength $(F_{1y})$ of 19-9DX (AMS-5534) Stamless Stret at Elevated Temperature		20	R
Figure 183,	Compressive Yal'd Strength (F <sub>CT</sub> ) of 19-*OX (AMS*5538) Stataless Smell at Elevated Temperature		. 20	ž
Figure 184,	Design Curve for Compressive Tied Strongth (F <sub>CY</sub> ) of 19-4DX (Ab.:-4534) Stommen Short at E-evaled Temperature		28	3
Figure 185.	Bearing Strength (Fig.) of 19-93X (AMS-2538) Stateless Sheel of Elevated Temperature		20	4
Figure 186.	Design Carve for Bearing Strength (Face) of 19-9DX (AMS-5530) Stambeto Small at Lievated Temperature		20	5
r - r 187,	Bearing Turisl Strength ( $F_{\rm locy}$ ) of 19-70X (Aldri-5518) Standens Swel at Devoted Temperature .	•	20	ri.
1 185.	Design Carrier for Bearing Total Strength (F <sub>M.Y</sub> ) of 19-90X (AMS-5516) Shankes Short at Elevated Temperature	٠	:0	•

و هو دوينون ده عدم

#### LIST OF ILL DITEATIONS

	·	hoge
Figure 189.	. Towarle Strongth (Ftm) of 19-90X (AMC-5539) Storaless Steel at Elevated Temperature	206
Figure 140.	Termin Strength (F <sub>13</sub> ) Expressed as a Percentage of Room-Temperature Tenaste Strength of 19-95X (A'd5-5539) Stainless Stee, at Elevated Temperature	299
Figure 191.	Device Corve for Tennile Strength (Fm) of 19-90X (AMS-5539) Sinualenn Steel at Elevated Temperature	210
Fapur (%),	Tensile Tuil Strength (Fty) of 19-9232(AMS-4539) Sainless Steel at Elevated Temperature	21.
Fapore 191.	Tensile See & Strength (Ft. \ Experienced as a Percentage of Room-Temperature Tensile Tank Strength of 18-400 (AMS-540) Statues a Steel of Ciercies Temperature	21:
Faguer 194.	Design Carve for Tennile Viold Strength (i.g.) of 17-70x (AMS-5519) Stainless Stock at Europe Temperature	21.5
Fagrace (M	Compressive Tield Strength (Fig.) of 19-90% (AMS-5519) Standers Street at Klevetad. Temperature	<b>(19</b>
Figure 1%	Draigs Cares for Compressive Tield Strength (2 cg) of 19-9DX (AM*-5539) Stambros Seed on Elevated Temperature	215
Fewe 160.	Bearing Strength (Fhrm) of 19-90X (AMS-5535) Standers Steel at Elevated Temperature	516
Figure 196.	Design Carve for Bearing Strongth (Fbru) of 19-9DX (AMS-5519) Stainless Steel at Elevated Tensperature	217
Fgure 149.	Bearing Toold Str. (1947) of 1947DX (AMS-5539) Stoubless Steel at Elevated Temperature	<b>218</b>
Figure 284.	Design Carve for Br. d Tield Strength (F <sub>key</sub> ) of 19-10X (AMS 9539) Stainless Stainles	247
Figure 271.	Tennale Strength (Frm) of A-29e Alley at Elevated (emperators	551
Figure 281.	Design Curve for Transle Streeg's (Tto) of A-206 Alloy at Sievated Transportance	222
Eguer 213.	Tenni's Tield Strength (Fty) of A-286 Alloy at Elevated Temperature	£2 .
Fagure 20L	Design Carve for Teasile York Strength ( $F_{1y}$ ) of A 20s Alloy at Klevnted Temperature	2.84
Egure 25.	Effect of Elevated Temperature on the Molules of Rigidity (G) of A-286 Allay	43
Figure 2%.	Effect of Elevated Temperature on Posson's Ratio (a) of A-286 Alloy	534
Tapine Nr.	Temssir Modelins (E) of A-296 Alony (Shret) at Elevated Temperature	เมา
Figure 286.	Temple Stress-Stress Curves for A-206 Alby Sheet	2.20
Fame 2 %.	Townsie and Toursie Tield Strengths ( $F_{E_0}$ and $F_{E_7}$ ) of Incomel "X" at Elevated Toursernbure	ΣЖ
<b>डिक्स</b> ण टे.क.	Tennal: and Tennals Total Strengths ( $F_{tx}$ and $F_{\tau y}$ ) of facuse). We at Elevated Temperature	m
Figure 211.	Tensile and Tennile Yorld Strengton $^{\ell}F_{00}$ and $F_{0\gamma}$ as decoded $^{\prime}X^{\circ}$ at Elevated Lengersburg	234
نائد	Effect of Sermin Rate on the Twosier Strength (Fig.) of become "X" at Elevated Taleperstants	1.35
Fapour 213.	Effect of Strain Rate on the Treater Yorld Strength (Fig.) of Income "X" at Elevator	294

#### LET OF LLUSTRATIONS (Contract)

Figure 214,	Design Curve for Tensule Strength (Fig.) of Incomit "X" at Elevated Temperature	THE PROPERTY OF
Figure 215.	Design Curve for Tennile Yield Strength (Fay) of Income! "It" at Exempted Temperature	
Sigure 216.	Compressive Yield Strength ( $F_{cy}$ ) of Income) "X" at Elevated Temperature	
Figure 217.	Orange Curve for Compressive Tield Strength ( $F_{\rm cy}$ ) of Incomet "X" of Elevates, Temperature $\sim$ -	
Figure 214	From and Bosong Tield Strengths ( $F_{\rm bry}$ and $F_{\rm bry}$ ) of Second "X" at EL raind Temperature	
Figure 219.	Dunign Carve for Bearing Strength (Fam.) of income! "X" or Elevated Temperature	
Figure 228.	Design Curve for Bearing Tield Strength (Fary) of Income! "X" at Elevated Tomperature	
Tigare 221.	Shear Strength ( $F_{pq}$ ) of Incodel "X" at Elevated Temperature	
Figure 21%	Dunya Curve for Shear Strength (Fan) of Income! "N" at Elevated Temperature	
Figure 223.	These Strongth (F pa) of income "X" at Ehrward Tel. paratings	
Fugure 224,	Design Curve for Shaar Strength (Fpq) of Income! "If" at Elevated Tamparature	
Figure 225,	Effect of Elevated Temperature on the Modulus of Rapetry (C) of Income "X"	
Figure 246.	Effect of Elevated Tamperature on Poisson's Ratio () for Income! "R"	
Figure 121	Tensile and Compressive Hoduli (E and $K_c$ ) of Incomel "X" at Elevated Temperature $(v_1,v_2,v_3,v_4,v_5,v_5)$	
Figure 214.	Tassile Strass-Strain Curves for Income! "X" at Room and Elevated Tomperature	
Figure 329.	Compressive Stress-Stram Curves for Incimel "X" at Room and Elevated Temperature	
Figure 230.	Tennile Stress-Strain Curve for Incoor! "R" or Room Temperature	
'Figure 231.	Tensile Strength (Ftu) of Stainless "W" Alloy at Element Temperature	
Figure 231.	Design Curve for Tensile Strength (Fig.) of Stainless "V" Alloy at Elevated Temperature	
Figure 231.	Teasile Yield Strength (Fig.) of Statuless "E" Alloy at Elevated Temperature	*
Figure 2H.	Design Curve for I castle Strength $\{F_{ty}\}$ of Stamless "W" Alloy at Elevated Tompeterard $\cdots \cdots \cdots$	<b>a</b>
firere 23%	Effect of Elevated Temperature on Possson's Raise () of Stanless "W" Alley	4
Figure 234.	Touctie Medults (E) of Standers "W" Alloy & Envelod Temperature	
Figure 237.	Tennile Strans-Strain Curve for Standens "H" Alloy at Room Temperature (Longitud and Property)	*
Figure 214.	Countle Strees-Strain Curve for Stantiess "W" Alloy at Rosen Yemperstere (Longitudinal Property)	24
Figure 23°.	Compréseive Stress-Stress Carve for Stambine "T" Alloy at Room Temperature (Longstoine).  Property)	M OF THE REAL PROPERTY.
Ligure 240.	Compressive Stress-Stram Carve for Staminss "T" Alloy at Room Temperature (Transment Property)	***
Espaire 241	Comparison of Tessia Strungths (F <sub>cs</sub> ) of Standard Strain and Super Alleys of Elevated. Tessperature	
	· \	

#### LIST OF ILLUSTRATIONS

		Page
Figure 24L	Comparison of Tensis Strengths (Fig.) of Precipitation-Startonoble Samiero Steele at Elevated Temperature	267
Figure 24),	Comparison of Tennie Avengths (Fig.) of AM-310 Stainless Steel at Elevated Temperature	
Figore 244	Comparison of Tenasic Strengths (Fpg) of 19-9DL Stambers Serel of Elevated Temperature	269
Figure 245,	Comparison of Compressive field Strengths (F <sub>cy</sub> ) of Sto-aless Steels and Super Alloys & Elevated Temperature	270
Fuguz e 24a.	Comparison of Bearing Strength's (Fare) of Statuless Steels at Elevated Temperature	271
Figure 247.	Comparison of Shear Strengths (Fam) of Statuless Steels at Elevated Temperature	272

و الله مردور الله عدم

#### MATERIALS-PROPERTY-DESIGN CRITERIA FOR METALS

PART 5. THE CONVENTIONAL SHORT-TIME, ELEVATED-TEMPERATURE PROPERTIES OF SELECTED STAINLESS STEELS AND SUPER ALLOTS

#### INTRODUCTION

The design strength properties of materials for airframe and missile fabrication presented in the ANC-5 (Air Force-Navy-Civil) Bulletin, "Strength of Metal Aircraft Elements". As the needs of designers in these fields crystallize, revisions of the Socument are required to introduce new information into the Bulletin or revise current information as more reliable data become available. The purpose of this investigation has been, broadly, to study various aspects pertinent to design criteria as suggested by the Materials Laboratory of Wright Air Development Center and to present the results of such studies in a format consistent with the present ANC-5 Bulletin for possible consideration by the ANC-5 Panel.

It should be emphasized that the recommended design curves included berein are not necessarily identical to any which will ultimately appear in ANC-5. Use of any data appearing herein is therefore subject to any roval by the cognizant procuring or certificating agency.

This report represents the fifth report in this series. The four previous reports are:

- (1) WADC TR 55-150, Part I, "Materials-Property-Design Criteria for Metals; Part I" (January, 1956).
- (2) WADC TR 55-150, Part 2, "Materials-Property-Design Criteria for Metals; Part 2, A Study of Methods of Presenting Creep Data for Airframe Design", by W. S. Hyler and H. J. Grover (July, 1955).
- (3) WADC TR 55-150, Part 3, "Materials-Property-Design Criteria for Metals; Part 3, Fatigue Evaluation of Magnesium Alloys", by W. S. Hyler and F. H. Lyon (June, 1956).
- (4) WADC TR 55-150, Part 4, "Materials-Property-Design Criteria for Metals; Part 4, Elastic Modeli: Their Deterunination and Limits of Application", by S. A. Gordon, R. Simon, and W. P. Achbach (August, 1956).

HARRICE P. Interior by sound on March L. 1851, for publications as a WADC Profession Report.

The purpose of this present study is to compile and present data on the conventional short-time, elevated-temperature properties of a number of stainless steels and heat-resistant alloys which are of current interest in airframe and missile fabrication. It is the aim of this report to provide a basis upon which it would be possible to supplement and revise the current issue of the ANG-5 Manual. It is not intended that any discrepancy exist between data contained in this report and data found in the current ANG-5 Bulletin. If such discrepancies are noted, the ANG-5 values of strength are to be used.

As a result of mutual agreement between representatives of the Materials Laboratory of Wright Air Development Center and of Bartelle Memorial Institute, the following commercial alloys are included in this report of stainless steels and heat-resistant alloys: (1) AISI 301 (half hard and full hard), (2) 422M, (3) 17-7PH (TH 1050 and TH 950), (4) AM-350, (5) 17-4PH, (6) 19-9DL, (7) 19-9DX, (8) A-286, (9) Inconel "X", and (10) Stainless "W". It was intended that data be presented on AISI 420 stainless steel; however, no pertinent data were found available for this material. A brief discussion of each alloy is found in the separate sections of this report.

For convenience, design curves from each of the specific material sections are summarized at the end of the report. Appendix a contains some material-comparison curves.

The authors wish to acknowledge the materials producers, airframe manufacturers, universities, research laboratories, and Government agencies listed below without whose assistance this investigation would not have been possible. A Bibliography is included in Appendix II.

Allegheny Ludlum Steel Corporation Armco Steel Corporation Babcock and Wilcox Tube Company Carpenter Steel Company Crucible Steel Company of America Haynes Stellite Company International Nickel Company Republic Steel Corporation Timken Roller Bearing Company United States Steel Corporation Universal Cyclops Steel Corporation Vanadium-Alloys Steel Company Boeing Airplane Company Chance Vought Aircraft, Inc. Douglas Aircraft, Inc. General Electric Company Glenn L. Martin Company North American Aviation, Inc. Armour Research Foundation

Southern Research Institute Titanium Metallurgical Laboratory (Battelle) University of California Cornell Aeronautical Laboratory Johns Hopkins Applied Physics Laboratory University of Michigan Research Foundation Syracuse University U. S. Department of Commerce (Aircraft Structures Branch) U. S. Department of Commerce (Materials Branch) National Advisory Committee on Aeronautics National Bureau of Standards Wright A.r Development Center (Materials Laboratory)

WADC TR 55-150 Pt 5

#### METHOD OF APPROACH

#### General Comments

As indicated in the "Introduction", a large number of sources were contacted in assembling the data from which the study was based. These included material producers, universities, research laboratories, Government agencies, and the open literature.

The properties of interest included tensile, compressive, shear, and bearing strengths. Assessment of these properties as a function of temperature, exposure time, strain rate, etc., was made, consistent with available data. For a number of alloys, considerable information was available on many of these properties; in other cases only a few properties had been evaluated. Thus, there developed in some cases large gaps which can be taken care of only by careful experimental programs.

The next several subsections relate in detail the approaches used in analyzing the large body of data. It should be pointed out that the goal was to provide conservative "design" curves of a form currently used in ANC.5. For alloys involving considerable data from a number of sources, procedures were adopted to account for differences in the data to prepare such design curves. Discussion of trends observed in the design curves was beyond the scope of the program.

Each alloy is considered in a major section of the report. This includes a brief description of the alloys and usual heat treatments, various graphs showing the relationships between mechanical properties and temperature, stress-strain curves, etc. A final major section contains the recommended design curves for the entire group of alloys.

In a number of cases mechanical properties were available from specimens sectioned transverse and longitudinal to the major working direction. In these cases both sets of properties were treated separately, In the following sections, curves treating transverse properties are so indicated in the graphs.

The standard structural symbols used throughout this report are:

Fin Ultimate tensile stress

 $\mathbf{F}_{tw}$  Tensile yield stress

F. Compressive yield stress

Fan Ultimate shear stress

WADC IR 55-150 Pt 5

Fhen Ultimate bearing stress

Forv Bearing yield stress

G Modulus of rigidity

μ Polenon's ratio

ksi Kips (1000 pounds) per square inch

psi Pounds per square inch

E Modulus of elasticity in tension; average ratio of stress to strain below proportional limit

Ec Modulus of elasticity in compression; average ratio of a stress to strain below proportional limit.

Fcy, Fsu, Fbru, and Fbry

#### Data From One Source

When data showing the effect of temperature (for any unique condition) on any of the above strength properties were available from only one source, no analysis was necessary. The data were presented in two ways. In the first presentation the actual stress value was plotted against temperature; in the second, the stress value as a percentage of the noom-temperature property was plotted against temperature. This second curve is in such format as to be residily inserted in the ANG-5 Bulletin on "Strength of Metal Aircraft Elements".

#### Data From More Than One Source

(Ftu). The actual stress values for this strength property are plotted on one graph against temperature for all sources of data. A second graph was prepared showing all the data from all sources plotted as a percentage of room-temperature ultimate tensile strength against temperature. This second graph also shows the design curve that had been approximated from the data. A final third graph was prepared showing only the recommended design curve in such format as to be readily inserted in the ANC-5 Bulletin.

WADC TR 55-150 Pt 5

(Fig. Fig. Far.) Far. and Far.). The actual stress values for these properties were plotted against temperature as for Fig. A working curve then was drawn which showed the ratio of the above properties to the ultimate tensile strength (Fig.) for the corresponding temperature (these working curves do not appear in this report). In some cases, a straight-line relationship or at least a realistic trend to the data was apparent. Values from the working curves then were utilized in establishing the relationship between the mechanical property and temperature. The determined property expressed as a percentage of the room-temperature property was plotted on a graph using data from all sources. Again, a separate graph was prepared indicating the recommended design curve in ANG-5 format. In those cases in which it was not possible to establish a realistic trend in the plots of the ratio of mechanical property to ultimate strength versus temperature, a conservative estimate was utilized in developing design curves.


### Treatment of Modulus of Elasticity (E and Ec) and Stress-Strain Data (Optimization Process)

#### General

The extensive data obtained for this study provided, in general, considerable variation in modulus of clasticity and in the shapes of stress-strain curves of various materials. The degree of scatter in modulus of clasticity is indicated for one material in Figure 1. To permit analyses of all the data for consistency, the following steps were takent

- (1) Determine the "optimum" modulus of elasticitytemperature relationship
- (2) Adjust the stress-strain curves to fit the optimura modulus for each particular temperature.

Determination of the optimum modulus of elasticity-temperature relationship was achieved by the method of polynomial regression (readily adaptable to IBM computation). This system provides (a) a method of approximating the underlying relationship of variables by means of a polynomial equation of the form



TENSILE MODULUS VERSUS TEMPERATURE FOR 2014-T6 CLAD ALUMINUM ALLOY FIGURE 1.

Ref. 58.

WADC TR 55-150 Pt 5

apere

Y, the dependent variable, is the modulus of elasticity in pei,

X, the independent variable, is the temperature in degrees F, and

Co, ---, Cn are the constant coefficients to be estimated;

(b) a method of estimating these coefficients for a polynomial of a given degree from a set of paired observations on the modulus of elasticity and temperature; and (c) a method of determining the degree of the polynomial equation which the data indicate is warranted and significant.

It was determined that a polynomial of first or, at most, the second degree would approximate all the data for the various materials and conditions:

- (a) Y = a + bX and
- (b)  $Y = a + bX + cX^2$ .

Figure 2 shows a curve approximated by this method and also shows the data from which the curve was derived,

The value thus determined for the modulus of elasticity at any given temperature was called the "optimized" value. Stress-strain curves for those materials and conditions for which an optimized modulus has been determined were adjusted so that the modulus agreed with the optimized value. The exception to this was that whenever the ANC-5 Bulletin reported a room-temperature modulus, thus value was used in preterence to any other.


#### Mathematical Details of Optimisation of Modulus Data

The effect of temperature on the modulus of elasticity can be represented by the equation

where

X is the temperature and

Y is the modulus of elasticity.



TENSILE MODULUS VERSUS TEMPERATURE FOR 2024-T81 ALUMINUM ALLOY FIGURE 2.

Ref. 58.

The symbol  $\hat{Y}$  means that Y is to be regressed on X; in other words,  $\hat{Y}$  is the estimated or predicted Y given the temperature X. The slope "b" of the regression equation is the regression coefficient and mathematically is

$$b = \frac{\Sigma xy}{\Sigma x^2} .$$

where x and y are the deviations from the mean  $\overline{X}$  and  $\overline{Y}$ .

The intercept "a" is approximated by a =  $\overline{Y}$ -b $\overline{X}$  where  $\overline{Y}$  =  $\frac{\overline{X}}{n}$  and  $\overline{X}$  =  $\frac{\overline{Z}X}{n}$ .

It can be seen from Figure 3 that Y is composed of three segments:  $\overline{y}$ ,  $\hat{y}$ , and dy- $\hat{x}$ . The quantity dy-x is the deviation from regression and is defined mathematically as

Using the relation  $Y = \overline{Y} + \hat{y} + dy \cdot x$  and  $\Sigma Y = \Sigma \overline{Y} + \Sigma \hat{y} + \Sigma dy \cdot x$ , squaring both sides results in

$$\Sigma Y^2 = \Sigma \bar{Y}^2 + \Sigma \hat{y}^2 + \Sigma dy \cdot x^2$$

the three product terms being zero.

The least-squares curve can be fitted to the data such that  $\Sigma dy \cdot x^2$  is a minimum and  $\frac{\Sigma \hat{y}}{\Sigma dy \cdot x}$  equals zero. Standard methods of analysis were utilized in determining how well the derived curve litted the data.




FIGURE 3. SCHEMATIC DIAGRAM OF QUANTITIES DESCRIBED IN OPTIMIZATION PROCESS

WADC TR 55-150 Pt 5

10

#### A151 301 STAINLESS STEEL (QQ-5-082, FS 301) (MIL-S-5059, Comp 301, half and ful! hard)

AISI 301 is an austenitic stainless steel which has the nominal composition shown in Table 1.

TABLE 1. NOMINAL CHEMICAL LOMPOSITION OF AISI 301 STAINLESS STEEL (QQ-S-682, FS 301)

	Weight
Zlement	Per Cent
Carbon	0,12
Chromium	17.00
Nickel	7,00
Iron	Balance

The relative proportion of chromium and nickel enables AISI 301 to work harden rapidly when cold worked; the steel is well suited to high-strength applications. Minimum representative mechanical properties of the half-hard and full-hard tempers are given in Table 2.

TABLE 2. MINIMUM REPRESENTATIVE MECHANICAL PROPERTIES OF AISI 301 STAINLESS STEEL (QQ-5-682, FS 301)


Property	Half Hard (AMS-5518C 1/2 Hard)	Full Hard (AMS-5519£ Hard)
Ultimate tensile (Ftu)	150,000 psi	185,000 pui
Tensile yield (Fty)	110,000 psi	140,000 psi
Elongation (e) in 2 inches	_	•
Thickness 0,015 anch and under	15 per cent	8 per cent
Thickness over 0,015 inch	18 per cent	9 per cent
Hardness	32 RC	41 RC

The temper conditions, half hard and full hard, are established by the tensile s'rength, which in this case is 150,000 psi minimum and 185,000 psi minimum, respectively.

The short-time, elevated-temperature data for the half-hard and full-hard tempers are shown in the following curves:

- (1) Tensile properties, Figures 4 through 11, and 36 through 42
- (2) Compressive properties, Figures 12 through 13
- (3) Bearing properties, Figures 14 through 19
- (4) Shear properties, Figures 20 through 21
- (5) Modulus of elasticity, Figures 22 through 30
- (6) Stress-strain curves, Figures 23 through 29, and 31 through 35

For 301 half hard, data are meager for compressive and shear properties; for 301 full hard only tensile properties are available.




TENSILE STRENGTH (F<sub>tu</sub>) of Aibi 301 (HALF HARD, STAINLESS STEEL AT Elevated temperature


FIGURE 4.

Ĭ,

WADC TR 55-154 Pt 5




EFFECT OF STRAIN RATE ON THE TENSILE STRENGTH ( $\mathbf{F}_{tu}$ ) OF AIS1 301 (HALF HARD) STAINLESS STEEL AT ELEVATED TEMPERATURE Raf. WADC 55-199, Part 2, p 53. FIGURE 9.



Tensile strength (F<sub>la</sub>), expressed as a percentage of room-temperature tensile strength, of aisi 301 (HALF HARD) stainless steel at elevated temperature FIGURE 6.

15

WADC TR 55-150 Pt 5



DESIGN CURVE FOR TENSILE STRENGTH (F<sub>11</sub>) OF AISI 301 (HALF HARD) STAINLESS STEEL AT ELEVATED TEMPERATURE Ref. 57, 141, 207. MOURE 7.

5





FIGURE 8. TENSILE TIELD STRENGTH (F<sub>ty</sub>) of AISI 301 (HALF HARD) STAINLESS STEEL AT ELEVATED TEMPERATURE



Effect of strain rate on the tensile yield strength  $(\mathbf{r_{ty}})$  of aisi 101 (half hard) stainless steel at elevated temperature Ref. WADC 55-199, Part 2, p 53. FIGURE 9.

18

WADC TR 55-150 Pt 5




FIGURE 10. TENSILE YIELD STRENGTH (F<sub>ty</sub>) OF AIS1 301 (HALF HAND) STAINLESS STEEL AT ELEVATED TEMPERATURE Raf. 57, 178, 207.






FIGURE 11. DESIGN CURVE FOR TENSILE YZELD STRENGTH ( $r_{\rm ty}$ ) of AIS1 301 (HALF HARD) STAINLESS STEEL AT ELEVATED TEMPERATURE Ref. 57, 141, 207.

WADC TR 55-150 Pt 5


この種であるととだけのな難でいっといいかに






DESIGN CURVE FOR COMPRESSIVE YIELD STRENGTH (F<sub>C</sub>) OF AISI 301 (11ALF HARD) STAINLESS STEEL AT ELEVATED TEMPERÂTURE Ref. 57, 176. FIGURE 13.


WADC TR 55-150 Pt 5



BEARING STAENGTH (F<sub>bru</sub>) OF AISI 301 (HALF HARD) STAINLESS STEEL AT ALDVATED TEMPERATÜRE FIGURE 14.



BEARING STRENGTH (F<sub>bru</sub>) EXPRESSED AS A PERCENTAGE OF GOM-TEMPERATURE BEARING STRENGTH OF AIS: 301 (HALF HARD) STAIN-LESS STEEL AT ELLVATED TEMPERATURE FIGURE 15.










FIGURE 17. BEARING YIELD STRENGTH (F<sub>bry</sub>) OF AISI 301 (HALF HARD) STAINLESS STEEL AT ELEVATED TEMPERATURE









DESIGN CURVE FOR SHEAR STRENGTH ( $F_{\rm eu}$ ) OF AISI 301 (HALF HARD) STAINLESS STEEL AT ELEVATED TEMPERÂTURE Ref. 207. FIGURE 21.




FIGURE 23. TENSILE STRESS-STRAIN CURVE FOR AISI 301 (HALF HARD) STAINLESS STEEL AT ROOM TEMPERATURE

Ref. 57.

WADC TR 55-151 FR 3




FIGURE 24. TENSILE STRESS-STRAIN CURVES FOR AISI 301 (HALF HART) STAINLESS STEEL AT 400 F Rel. 对。 33 WADC TR 55-150 Pt 5




FIGURE 25. EFFECT OF TRAIN RATE ON THE TENSILE STRESS-STRAIN CURVE OF AMI 301 (HALF HARD) STAINLESS STEEL AT 400 F

WADC TR 55-150 21 5 WADC 55-199, Part 2, p 59.





FIGURE 26. TENSILE STRESS-STRAIN CURVES FOR AISI 301 (HALF HARD) STADDLESS STEEL AT 600 F Ref. 57.






FIGURE 28. TENSILE STRESS-STRAIN CURVES FOR AISI 301 (HALF HARD) STAINLESS STEEL AT 1000 F




FIGURE 29. TENSII E STRESS-STRAIN CURVES FOR ALSI 301 (HALF HARD) STAINLESS STEEL AT 1200 F




FIGURE 30. COMPRESSIVE MODULUS (E $_c$ ) OF ABI 301 (HALF HARD) STAINLESS STEEL AT ELEVATED TEMPERATURE




FIGURE 31. COMPRESSIVE STRESS-STRAIN CURVE FOR AISI 301 (HALF MARIN STAINLESS STEEL AT ROOM TEMPERATURE




FIGURE 32. COMPRESSIVE STRESS-STRAIN CURVES FOR AISI 301 (HALF HARD) STAINLESS STEEL AT 400 F




FIGURE 33. COMPRESSIVE STRESS-STRAIN CURVES FOR AISI 361 (HALF HARD) STAINLESS STEEL AT 600 F




FIGURE 34. COMPRESSIVE STRESS-STRAIN CURVES FOR AISI 301 (HALF HARD) STAINLESS STEEL AT 800 F

Zel 57. WADC TR 55-150 Pt 5







FIGURE 35. COMPRESSIVE STRESS-STRAIN CURVES FOR AISI 301 (HALF HARD) STAINLESS STEEL AT 1000 F

Ref. 57. WADC TR 55-150






Effect of strain rate on the tensile strength  $\{F_{tu}\}$  of aisi  $3^{n}$ i (full hard) stainless steel at elevated temperature Ref. WADC 55-19/), Part 2, p 60. FIGURE 37.



Tenbile btrength (f<sub>tu</sub>) expressed as a percentage of roum-temperature tensile strength of aisi 301 (full hard) stain-less btrel at elevated temperature FIGURE 38,



Design curve for tensile strength (F<sub>tu</sub>) of Aisi 301 (full Hârd) Stainless steel at elevated temperature Ref. 141, 178, 360. FIGURE 39.






FIGURE 40, TENSILE YIELD STRENGTH ( $F_{iy}$ ) OF AISI 301 (FULL HARD) STAINLESS STEEL AT ELEVATED TEMPERATURE






EFFECT OF STRAIN RATE ON THE TENSILE YIELD STRENGTA (F<sub>ty</sub>) OF AISI 301 (FULL HARD) STAINLESS STEEL AT ELEVATED TEMPERATUPE FIGURE 41.

WADC 55-199, Part 2, p 60,

50

FADC TR 55-150 Pt 5



desion curve for terbile yield strength  $(\mathbf{r}_{\mathbf{t}_{\mathbf{y}}})$  of abi 301 (full hard) stainless steel at elevated temperature Raf. 360. FIGURE 41.

WADCITE SS-150 Pt 5

## 422M STAINLESS STEEL

The AISI 400 series stainless steels, as a general rule, retain high-strength properties obtained by heat treatment up to above \$00 F before embrittlement occurs. A modification of the AISI 470 type resulted in the ferritic 422 grade, which has proven suitable for service around 1000 F. A further improvement resulted in a modified 422, which is similar in characteristics to 422 but possesses appreciably better elevated-temperature strength. The nominal chemical composition of 422M is given in Table 3.

TABLE 3. NOMINAL CHEMICAL COMPOSITION OF 422M STAINLESS STEEL

Element	Weight Per Cent
Carbon	0, 28
Manganese	0.84
Silicon	0.24
Nickel	0.20
Chromium	11.60
Vanadium	0.49
Tungsten	1.76
Molybdenum	2, 24
lron	Balance

Alloy 422M is referred to as a ferritic grade aithough it is heat treatable. A typical heat treatment (such as austenitizing at 2000 F, oil quenching, and tempering at 1200 F for 2 hours) results in a microstructure of tempered martensite plus about 10 per cent ferrite. The hardness of the steel after this heat treatment is about Rockwell C 38. Typical short-time, elevated-temperature properties of 422M are shown in the following curves:

Tensile properties, Figures 43 through 46

Stress-strain curves, Figures 47 through 57

For 422M, data are completely lacking for compressive, bearing, and shear strengths, and modulus of clasticity and stress-strain curves at elevated temperatures.





FIGURE 43, TENSILE STRENGTH (F<sub>tu</sub>) of 422M STAINLESS STEEL AT ELEVATED TEMPERATURE



design curve for tensile strength  $(\mathbf{F}_{\mathbf{h}})$  of 422m stainless steel at elevated temperature FIGURE 44.

WADC IR \$5-150 Pt 5




Figure 45. Tensile tield strungth (F<sub>ty</sub>) of 422m stainless steel at elevated temperature




Figure 46. Design curve for tensile yield strength ( $\mathbf{r}_{ty}$ ) of 422m staulless streel at elevated temperature

54

WADC TR 55-150 Pt 5

と言語でしていても自動をいったなり自動なななななない。




FIGURE 47. TENSILE STRESS-STRAIN CURVES FOR 422M STAINLESS STEEL AT ROOM TEMPERATURE

Rel. 345.

WADC TR 55-150 Pt 5




FIGURE 46. TENSILE STRESS-STRAIN CURVE FOR 422M
STAINLESS STEEL AT ROOM TEMPERATURE

WADC TR 55-150 Pt 5




FIGURE 49. TENSILE STRESS-STRAIN CURVE FOR 422M STAINLESS STEEL AT ROOM TEMPERATURE

WADC TR 55-150 Pt 5 Ref. 349.




FIGURE 51. TENSILE STRESS-STRAIN CURVE FOR 422M STAINLESS STEEL AT ROOM TEMPERATURE

WADC TR 55-150 P




FIGURE 51. TENSILE STRESS-STRAIN CURVES FOR 422M STAINLESS STEEL AT ROOM TEMPERATURE Ref. 349.

WADC TR 55-150 Pt 5






FIGURE 52. TENSILE STRESS-STRAIN CURVES FOR 422M STAINLESS STEEL AT ROOM TEMPERATURE

Rel. 349. WADC TR 55-150 Pt 5




FIGURE 53. TENSILE STRESS-STRAIN CURVES FOR 422M STAINLESS STEEL AT ROOM TEMPERATURE Rel. 349.

WADC TR 55-150 Pt 5




FIGURE 54. TENSILE STRESS-STRAIN CURVE FOR 422M STAINLESS STEEL AT ROOM TEMPERATURE Ref. 349.

WADC TR 55-150 Pt 5




FIGURE 55. TENSILE STRESS-STRAIN CURVES FOR 422M STAINLESS STEEL AT ROOM TEMPERATURE

Ref. 349. WADC TR 55-150 Pt S




FIGURE 56. TENSILE STRESS-STRAIN CURVES FOR 422M STAINLESS STEEL AT ROOM TEMPERATURE

WADC TR 55-150 Pt 5 66




FIGURE 57. TENSILE STRESS-STRAIN CURVE FOR 422M STAINLESS STEEL AT ROOM TEMPERATURE

Ref. 349.

WADC TR 55-150 Pt 5

## 17-77 STAINLESS STAEL (AMS-5528)

17-7PH is a precipitation-hardenable stainless steel that has good strength properties up to 700 F. The composition is balanced so that, as unnealed, the alloy is sustenitic. Hardening is accomplished by a double heat treatment. The first heat treatment is at 1500 F to precipitate curomium carbides and thereby render the alloy unstable; then, on cooling to below 250 F the austenite transforms to martenaite (with transformation escentially complete at 60 F). The second heat treatment is at 950 to 1050 F to promote precipitation of what are thought to be aluminum compounds in the martenaitic matrix(358). The nominal chemical composition for 17-7PH is shown in Table 4, and minimum tensile properties are given in Tuble 5.

TABLE 4. NOWINAL CERMICAL COMPOSITION OF 17-7TH STAINLESS STEEL (AMS-5528)

Element	Velght Per Ceni
Chromium	17.00
Mickel	7.00
Alminus	1,20
Irue	Balance

TABLE 5. MINIMUM MECHANICAL PROPERTAINS OF 17-7FH STAINLESS STREET

Property	Condition (TH-1050) (AMS-5528)	Condition (TH-950) No Specification ATBILABLE
Timete Tensile(Fgu	) 160,000 pei	185,000 pei
Tensile Yield (Fgy)	150,000 pei	165,000 pei
Licongation(e) in 2 i	nebes 6 per cent	6 per sest

•See bibliographs in Appendix II.

## Condition TH 1050

Condition TH 1050 is developed in steps from Condition A and then Condition I. The steel is first solution annealed at 1950 F a 25 F for 3 minutes per each \$\delta\$, I inch of thickness. This treatment drives the chromium carbides into solution in the austenite, thus stabilizing the austenite against martenistic transformation and effectively depresses the Mg temperature. This brings the steel to Condition A. The steel is then treated at 1400 F a 25 F for 90 minutes which results in Condition I. The steel is now conditioned so that sufficient austenite transformation can be obtained at 60 F on cooling. Finally, Condition TH 1050 is attained by precipitation hardening at 1050 F.


## Condition TH 950

Condition TH 950 is developed in the same way, except that the final precipitation hardening takes place at 950 F.

The short-time, elevated-temperature properties of 17-7PH are shown in the following curves:


- (1) I maile properties, Figures 55 through 63 and 66 through 89
- (2) Compressive properties, Figures 64 and 65
- (3) Bearing properties, Figures có through 69
- (4) Shear properties, Figures 70 and 71
- (5) Modulus of elasticity, Figures 72, 78, and 85
- (6) Stress-strein curves, Figures 73 through 77, 79 through 83, and 85.

Design properties of 17-7PH (TH 1050) are fairly well established, but only tensile properties are available for 17-7PH (TH 950).




TENSILE STRENGTH ( $\mathbf{F}_{tu}$ ) OF 17-7PH (TH 1050) STAINLESS STEEL AT ELEVATED TEMPERATURE FLIJURE 58.


WADC TR 55-150 Pt 5




eppect of btrain rate on tid: tensile strength  $(r_{tu})$  of  $(7-7P)^{\mu}$  (th 1050) stainlens steel at elevated temperature Rof. WADC 56-199, Part 2, p 74. FIGURE 89,




DESIGN CURVE FOR TENSILE STRENGTH ( $F_{tu}$ ) OF 17-7PH (TH 1050) STAINLESS STEEL AT ELEVATED TEMPERATURE FIGURE 60.






effect of strain rate on the tensile yield strength ( $\mathbf{f}_{ty}$ ) of 17-7PH (th 1050) strinless steel at elevated temperature Ref. WADC 55-199, Part 2, p 74. FIGURE 62.

WADC TR 55-150 Pt \$




Design curve for tensile yield strength (F<sub>ty</sub>) of 17-7PH (TH 1050) stainless steel at elevated temperature FIGURE 63.

WADC TR 55-056 Pt 5



COMPRESSIVE YIELD STRENGTH ( $F_{cv}$ ) OF 17-7PH (TH 1050) STAINLESS STEEL AT ELEVATED TEMPERATURE FIGURE 64.

WADC TR 55-150 Pr 5






FIGURE 66, BEARING STRENGTH (FULL) OF 17-7PH (TH 1050) STAINLESS STEEL AT BLEVATED TEMPERATURE

WADC TR 55-150 Pt 5

7.





FIGURE 61. DESIGN CURVE FOR BEARING STRENGTH (F<sub>bru</sub>) of 17-7PH (TH 1050) 8TAINLESS STEEL AT ELEVATED TEMPERATURE

YADO TR SS-150 Pt 5


\$ \$ DNorth American -Design curve 1200 + WADC e/D=1.5 000 Temperature, # 00 900 3 800 Bearing Yield Strength (F<sub>DA</sub>),0000 psi 8

Bearing yield strength (F<sub>bry</sub>) of 17-7PH (TH 1050) btainless steel at elevated temperature FIGURE 68.


WADC TR 55-150 Pt \$



WADC TR 55-150 Pt 5



BHEAR STRENGTH (F<sub>BU</sub>) OF 17-7PH (TH 1050) STAINLERS STEEL AT ELEYATED TEMPERATURE FIGURE 70.






FIGURE 12. TENSILE MODULUS (E) OF 17-1PH (TH 1050) STAINLESS STEEL AT ELEVATED TEMPERATURE Rof. 396.




FIGURE 75. TENSILE STRESS-STRAIN CURVE FOR 17-7PH (TH 1050) STAINLESS STEEL AT ROOM VEHICLERATURE

Ref. 356, WADO TR 55-150 Pt 5




FIGURE 74. TENSILE STRESS-STRAIN CURYES FOR 17-7PH (TH 1450) STAINLESS STEEL AT 400 F

Ref. 356, WADC TR 55-150 Pt 5




FIGURE 75. TENSILE STRESS-STRAIN CURVES FOR 17-7PH (TH 1050) STAINLESS STEEL AT 600 F

Raf. 356. WADC TR 55-150 Pt 5




FIGURE 76. TENSILE STRESS-STRAIN CURVES FOR 17-7PH (TH 1050) STAINLESS STEEL AT 800 F

Re£ 356,

WALC TR 55-150 Pt 5





FIGURE 77. TENSILE STRESS-STRAIN CURVES FOR 17-7PH (TH 1050) STAINLESS STEEL AT 900 F

Ref. 354.

WADC IR 35-190 Pt 5



COMPRESSIVE MODULUS (E<sub>c</sub>) OF 17-7PH (TH 1050) STAINLESS STEEL AT ELEVATED TEMPCRATURE Ref. 356, FIGURE 78.

--

WADC TA SS-150 Pe S




FIGURE 19. COMPRESSIVE STRESS-STRAIN CURVE FOR 17-7PH (THE 1050) STABILISS STEEL AT ROOM TEMPERATURE

Ref. 354

WADC TR 55-150 Pt 5




FIGURE 80. COMPRESSIVE STRESS-STRAIN CURVES FOR 17-7PH (TH 1050) STAINLESS STEEL AT 400 F

Ref. 356.




FIGURE 81. COMPRESSIVE STRESS-STRAIN CURVES FOR 17-7PH (TH 10:0) STAINLESS STEEL AT 600 F

Ref. 356.

WADC TR 55-150 Pt 5




FIGURE 82. COMPRESSIVE STRESS-STRAIN CURVES FOR 17-7PH (TH 1050) STAINLESS STEEL AT 800 F

Ref. 356.





FIGURE 83. COMPRESSIVE STRESS-STRAIN CURVES FOR 17-7PH (TH 1050) STAINLESS STEEL AT 900 F

Rel. 356.



compressive modulus ( $\epsilon_c$ ) of 11-1PH stainless steel at elevated temperature FIGURE 84.

R.C. 207.

96

WALK TR 55-150 Pt 5





FIGURE 85. COMPRESSIVE STRESS STRAIN CURVES FOR 17-7PH STAIN-LESS STEEL AT ROOM AND ELEVATED TEMPERATURE

Ref. 207.

WADC TR 55-150 Pt 5

5.0








FIGURE 81. DESIGN CURVE FOR TENSILE STRENGTH (F<sub>11</sub>) OF 17-1PH (TH 950) STAINLESS STEEL AT ELEVATED TEMPFRATURE Ref. 215.



tensile yield strength (F<sub>ty</sub>) of 17–1PH (TH 950) btainl**ess** steel at elevated temperature FIGURE 88.



design curve for tensile yield strength ( $F_{(y)}$ ) of 17-7PH (th 950) stainless steel at elevated temperature Ref. 215. FIGURE 89.

## AM-350 STAINLESS STEEL

AM-350 is a precipitation-hardenable stainless steel having the nominal composition shown in Table 6.

TABLE 6. NOMINAL CHEMICAL COMPUSITION OF AM-350 STAINLESS STEEL

Element	Weight Per Cent
Manganese	0.50
Silicon	0.40
Chromium	17.00
Nickel	4,20
Molybdenum	2,75
Iron	Balance

As annealed, AM-350 is austenitic and, like other austenitic stainless steels, is soft and ductile in this condition. The composition has been controlled so that the martensite transformation temperature is below 32 F but above -80 F. Hardening is accomplished by "deep freezing" the annealed alloy to -100 F (i.e., below the M<sub>2</sub> temperature, which allows the austenite-martensite transformation to proceed), followed by tempering the martensitic structure at about 750 F. It is pointed out that at 750 F no precipitation occurs but that the desired atrength properties are obtained from the tempering of the martensite. A double-aging treatment is a second heat-treating method.


Annealing temperature has a noticeable effect on the properties obtained after aging; 1750 F is the optimum annealing temperature for the "deep-freeze and temper" treatment, while 1950 F is preferred for the "double-age" heat treatment.


The short-time, elevated-temperature properties of AM-350 are shown in the following curves:


- (1) Tensile properties, Figures 90 through 93, 95 through 98, and 100 through 103.
- (2) Modulus of elasticity, Figures 94, 99, 104, 109, and 112,
- (3) Shear properties, Figures 105 and 106.

- (4) Compressive properties, Figures 10? and 108
- (5) Stress-strain curves, Figures 110, 111, and 115 through 125.

Data on all strength properties except bearing strength are available on AM-350.









WADC TR 55-150 Pt 5

Tensile yield btrength ( $\mathbf{r}_{ty}$ ) of AM-150 bt-liness bteel (sulution Heat treated at 1700 f) at elevated temperatule


MOURE 92.




No 1. 351.




TENSILE MODULUB (E) OF AM-350 STAINLESS STEEL (SOLUTION HEAT TREATED AT 1700 F) AT ELEVATED TEMPERATURE Ref. 558. FIGURE 94.






DESIGN CURVE FOR TENSILE STRENGTH ( $\mathbf{F_{to}}$ ) of am-350 stainless styel (solution heat treated at 1750 f) at elevated temperature Ref. 358. FIGURE 96.




Lil

Tensile yield strength  $(Y_{i,y})$  of am-190 stainless steel. (Solution heat treated at 1780 F) at eleypted temperature Rot. 358. FIGURE 97.

WADC TR 15-450 Pt 5



design curve for tensile yield strength ( $\mathbf{F}_{\mathbf{t}'}$ ) of am-350 stainless steel (solution heat trented at 1750 f) at elevated temperature Raf. 35P. FIGURE 98.






FIGURE 100, TENSILE STRENGTH (Ftu) OF AM-350 STAINLESS STEEL (JOUBLE AGED) AT ELEVATED TEMPERATURE Ref. 358.




FIGURE 101. DESIGN CURVE FOR TENSILE STRENGTH ( $\Gamma_{10}$ ) Of AM-350 STAINLERS STEEL (DOUBLE AGED) AT BLEVATED TEMPERATURE Ref. 388.

Per Cent Fig at Room Temperature




FIGURE 102. TENSILE YIELD STRENGTH ( $F_{ty}$ ) OF AM-350 STAINLESS STREL (BOUBLE AGED) AT ELEVATED TEMPERATURE Ref. 358,

YADC TIL 55-150 Pt 5








FIGURE 10). DESIGN CURVE FOR TENSILE YIELD STRENGTH (Fty) OF AM-350 STAINLESS STEEL (DOUBLE AGED) AT ELEVATED TEMPERATURE Ref. 358.





OP3












design curve for compressive yield strength ( $r_{\rm cy}$ ) of AM-350 stainless steel at elevated temperature FIGURE 108.






FIGURE 110. TENSILE STRESS-STRAIN CUEVES FOR AM-350 STAINLESS STEEL AT ROOM TEMPERATURE




FIGURE 111. TENSILE STRESS-STRAIN CURVES FOR AM-350 STAIN-LESS STEEL AT ROOM AND ELEVATED TICLERATURE




Figure 112. Compressive modulus (E.) of AM-350 stainless steel at elevates temperature




FIGURE 113. COMPRESSIVE STRESS-STRAIN CURVES FOR AM-350 STAINLESS STEEL AT BOOM AND ELLEVATED TEXCPERATURE
WADO TR 55-150 Pt 5 127




FIGURE 114. EFFECT OF ANNEALING AT 1700 F AND 1750 F ON THE TENTILE STRESS-STRAIN CURVE OF AM-350 STAINLESS STEEL AT ROOM TEMPERATURE (LONGITUDINAL PROPERTY)

Ref. 85. WADC TR 55-150 Pt 5




FIGURE 115. EFFECT OF ANNEALING AT 1700 F, 1750 F, AND 1900 F ON THE TENSILE STRESS-STRAIN CURVE OF AM-150 STAINLESS STEEL AT ROOM TEMPERATURE (TRANSVERSE PROPERTY)
Ref. 35.




FIGURE 116. EFFECT OF ANNEALING, AT 1700 F, 1750 F, 1800 F,
AND 1900 F SUBZERO COOLING, AND TEMPERING ON
THE TENSILE STRESS-STRAIN CURVE OF AM-350
STAINLESS STEEL AT ROOM TEMPERATURE
(LONGITUDINAL PROPERTY)
Ref. 85.




FIGURE 117. EFFECT OF ANNEALING, SUBZERO COOLING, AND
TEMPERING ON THE TENSILE STRESS-STRAIN
CURVE OF AM-350 STAINLESS ST L AT ROOM
TEMPERATURE (TRANSVERSE PROPERTY)

Ref. 15.

WADC TR 55-150 Pt 5




FIGURE 118. EFFECT OF ANNEALING, AT 1700 F, 1750 F, 1800 F,
AND 1900 F AIR COOLING, AND DOUBLE AGING ON
THE TENSILE STRESS-STRAIN CURVE OF AM-350
STAINLESS STEEL AT ROOM TEMPERATURE
(LONGITUDENAL PROPERTY)

WADO TR 55-130 PLS





FIGURE 119. EFFECT OF ANNEALING, AT 1700 F, 1750 F, AND 1900 F
AIR COOLING, AND DOUBLE AGING ON THE TENSILE
STRESS-STRAIN CURVE F AM-350 STAINLESS STEEL AT
ROOM TEMPERATURE (TRANSVERSE PROPERTY)

Ref. 65. WADC TR 55, "50 Pt 5






FIGURE 120. EFFECT OF ANNEALING AT 1700 F ON THE COMPRESSIVE STRESS-STRAIN CURVE OF AM-350 STAINLESS STEEL AT ROOM TEMPERATURE (LONGITUDINAL PROPERTY)




FIGURE 121. EFFECT OF ANNEALING AT 1700 F ON THE COMPRESSIVE STRESS-STRAIN GUEVE OF AM-350 STAINLESS STEEL AT ROOM TEMPERATURE (TRANSVERSE PROPERTY)




FIGURE 122. EFFECT OF ANNEALING, SUBZERO COOLING, AND TEMPERING ON THE COMPRESSIVE STRESS-STRAIN CURVE AM-350 STAINLESS STEEL AT ROOM TEMPERATURE (LONGITUDINAL PROPERTY)

Rel 85.




FIGURE 123. EFFECT OF ANNEALING, SUBZERO COOLING, AND TEMPERING ON THE COMPRESSIVE STRESS-STRAIN CURVE OF AM-350 STAINLESS STEEL AT ROOM TEMPERATURE (TRANSVERSE PROPERTY)

Ref. 85, WADC TR 55-150 Pt 5

The state of the s




FIGURE 12.. EFFECT OF ANNEALING AT 1700 F AND 1750 F AND
STANDARD DOUBLE AGING ON THE COMPRESSIVE
STRESS-STRAIN CURVE OF AM-350 STAINLESS STEEL
AT ROOM TEMPERATURE (LONGITUDINAL PROPERTY)

W.LDC TR 5/=150 Pt 5




FIGURE 125. EFFECT OF ANNEALING AT 1700 F AND 1750 F AND STANDARD DOUBLE AGING ON THE COMPRESSIVE STRESS-STRAIN CURVE OF AM-350 STAINLESS STEEL AT ROOM TEMPERATURE (TRANSVERSE PROPERTY)

Raf. 85. WADC TR 55-150 Pt 5

## 17-4PH STAINLESS STEEL

17-4PH has a composition that has been termed a "severely unbalanced" AISI 301. The austenitic phase is so unstable that it transforms to martensite at about 200 to 300 F, upon cooling from the annealing temperature. Aging at about 900 to 1000 F picmotes precipitation of intermetallic compounds from the martensite. The nominal composition of 17-4PH is shown in Table 7.


TABLE 7. NOMINAL CHEMICAL COMPOSITION OF 17-4PH STAINLESS STEEL

Element	Weight Per Cent
Chromium	16_50
Nickel	4.00
Copper	4.00
Columbium (niobiem, + tantalum	0.35
Carbon, maximum	0.97
lroz	Balance

The short-time, elevated-temperature properties of 17-4PH are shown in the following curves:

- (1) Tensile properties, Figures 126 through 129 and 138
- (2) Compressive properties, Figures 130 and 131
- (3) Shear properties, Figures 132 and 133
- (4) Bearing properties, Figures 134 through 137
- (5) Modulus of elasticity, Figures 139 and 141
- (6) Stress-strain curves, Figures 140 and 142

Data are available on 17-4PH for all surveyed strength properties.






Figure 127. Design curve for tensile strength ( $\mathbf{r}_{tu}$ ) of 17-4PH stainless stellatelatelyated temperature

Ref. 207, 215, 358.

142





Figure 129. Design curve for tensile yield strength  $\{r_{iy}\}$  of 17-4PH stanless steel at elevated temperature Ref. 107, 215, 380,

WADC TR 55-150 Pt 5

TO SEE THE PROPERTY OF THE PRO



compressive yield strength ( $\mathbf{r}_{,\,\,\phi}$ ) of 11-4PII stainless steel at elevated temperature FIGURE 130.

Ref. 207.

145

WADC TE 55-250 PE 5







Figure 131. Design curve for compressive yield strength ( $r_{\rm cy}$ ) of 17-4PH stanless stell at elevated temperature Rof. 207.











FIGURE 139. DESIGN CURVE FOR BEARING STRENGTH (F<sub>bru</sub>) of 17-4PH STAINLESS STEEL AT ELEVATED TEMPERATURE

Ref. 207.

WADC TR 55-150 Pt 5




Braring Yield Strength (F<sub>bry</sub>) of 17-4PH Stainless Steel at Elinvated Temperature

Ref. 207,

151

WADC TR 55-150 Pt 5


いいことは国内にないできょう。



DESIGN CURVE FOR BEARING YIELD STRENGTH (F<sub>bry</sub>) of 17-4PH STAINLESS STEEL AT ELEVATED TEMPERATURE FIGURE 137.

Rof. 207.

152







FIGURE 139. TENSILE MODULUS (E) OF 17-4PH STAINLESS STEEL FORGING AT ELEVATED TEMPERATURE Ref. 192.



:54





FIGURE 140. TENSILE STRESS-STRAIN CURVES FOR 17-4PH STAINLESS STEEL FORGING AT ROUM AND ELLEVATED TEMPERATURE

Ref. 192. WADC TR 55-150 Pt 5



COMPRESSIVE MODULUS (Eq.) OF 17-4PH STAINLESS STEEL FORGING AT ELEVATED TEMPERATURE FIGURE 141.

Rof. 192.

156




FIGURE '42... COMPRESSIVE STRESS-STRAIN CURVES FOR 17-4PH
STAINLESS STEEL FORGING AT ROOM AND ELEVATED
TEMPERATURE
Ref. 192.

WADC TR 55-150 Pt 5

## 19-90L ALLUY (AMS-5527A)

Alloy 19-90L is a chromium-nickel alloy that has a predominantly austenitic structure. The typical chemical composition is given in Table 8.

TABLE 6. TYPICAL CHEMICAL COM-POSITION OF 19-9DL HEAT... RESISTANT ALLOY (ALS-5526B) (AMS-5527A)

Element .	Weight Per Sent
Carbon	9.30
Manganese	1,25
Silicon	0.55
Nickel	9.00
Chromie.	17.00
Molybdenum	1,25
Tuesten	1,25
Columbium + tantalum	0_40
Titanium	0.29
Iron	Balance

The alloy 19-9DL is usually used in the ametaled or stress-relieved condition at temperatures below approximately 1300 F. For service above approximately 1300 F, the alloy is solution treated and aged. Other conditions are useful for numerous applications. Table 9 gives the minimum mechanical properties of 19-9DL after solution heat treating at 1800 F ±25 F and air cooling.

TABLE 9. MINIMUM MECHANICAL PROPERTIES OF 19-90L ALLOY (AMS-5526B)

Property	
Ultimate tensile (Ftu)	95,000-120,000 pai
Irasiie yield (Fty)	45,000 psi (musersam)
Elongation (e) in 2 inches	30 per cess (massages)

Table 10 gives the minimum mechanical properties of 19-70L after stress relieving at 120v F ± 25 F, and air cooling.


TABLE 10. MINIMUM MECHANICAL PROPERTIES OF 19-9DL ALLOY (AMS-5527A)


Property	
Ultimate tensile (Ftu) Tensile yield (Fty)	125, 000 psi (minimum) 90, 000 psi (minimum)
Elongation (e) in 2 inches	12 per cent (minimum)


The short-time, elevated-temperature properties of 19-9DL are shown in the following curves:

(1) Tensile properties, Figures 143 through 176.

Although the effect of many conditions and heat treatments on the tensile strength of 19-9DL has been investigated, no information is available on other design properties.









tensile yield strength  $(\mathbf{r}_{ty})$  of 19-9DL stainless steel (anneal:ed) at elevated temperature Ref. 16. FIGURE 145.

346




DESIGN CURVE FOR TENSILE YIELD STRENGTH ( $\mathbf{F}_{iy}$ ) OF 19-9DL STAINLESS STEEL FIGURE 146.

Rof. 16.




TEVSILE STRENGTH (F<sub>14</sub>) OF 19-9DL STAINLESS STEEL (COLD ROLLED) AT ELEVATED TEMPERATURE Rof. 16. FIGURE 147.



Design curve for tensile strength  $(r_h)$  of 19-9DL stainless steel (COLD rolled) at elevated temperature FIGURE 148.


Aof. 16.



Tensii.e Yield byrength  $(F_{ty})$  of 19-4dl stainless stell (Cold Rolled) at elevated temperature Rof. 16. FIGURE 149,


WADIC TR. 55 -1140 PR 5


TO A CONTRACTOR OF THE PROPERTY OF THE PROPERT




Tensile strencth ( $\mathbf{F}_{tu}$ ) of 19-9dl stainless steel (hot rolled and stress relieved) at elevated temperature Rei. 211. FIGURE 151.

WADC TR 55-150 Pt 5






TENSILE YIELD STRENGTH (F<sub>IV</sub>) OF 19-9DL STAINLESS STEEL (HOT ROLLLD AND STRESS RELIEVED) AT ELEVATED TEMPERATURE Rof. 241. FIGURE 153.





design curve for tensile yield strength  $(F_{\rm by})$  of 19-9D1. Stainless steel (not rolled and stress relieved) at elevated temperature Ref. 241. FIGURE 184.

WADC TR 55-150 Pt \$




Tensile strength ( $\mathbf{F}_{tu}$ ) of 19-4dl stainless steel (hot forged) at elevated temperature Ref. 29, Data Sheet 4. FIGURE 195.






Tensile strength ( $\mathbf{F}_{tu}$ ) of 19-4dl stainless steel (hot rolled) at elevated temperature FIGURE 147.

Ref. 29, Data Sheet 23.



design curve for tensile strength  $(\mathbf{F}_{tt})$  of 19-9dl stainless steel (hot rolled) at elevated temperature Ref. 29, Data Sheet 23. FIGURE 158.





12.00A 10.00 St. 50.00







Figure 159. Tensile strength ( $\mathbf{F}_{\mathbf{t}_{\mathbf{t}_{\mathbf{t}}}}$ ) of 19-9dl stainless steel (hot rolled) at elevated temperature

Ref. 29, Deta Sheet 22.




Design curve for tensile strength ( $\mathbf{r}_{i,j}$ ) of 19-4DL stainless steel. (Hot rolled) at elevated temperature Raf. 29, Dath Shoot 32. FIGURE 160.






Tensile yield strength  $(\mathbf{F}_{\mathbf{t}_y})$  of 19-4DL stainless steel (hot rolled) at elevated temperature Ref. 29, Data Sheet 22, FIGURE 161.

- (25) Ross, A. O., "Determination of Bouncary-Layer Transition Regiments Numbers by Surface-Temperature Measurements of a 10-Degree Come in Various NACA Supersonic Wind Tunnels", NACA TN 3020, October 1953, 26 pages.
- (15) Miller, R. F., and Heger, J. J., "The Strongth of Wrought Steels at Elevated Temperatures", ASTM-ASME Joint Committee, ASTM Special Publication No. 160 (1950).
- (27) Simmons, W. F., and Cross, H. C., "The Elevated Temperature Properties of Stainless Steels, ASIM-ASME Joint Committee ASIM Special Publication No. 124 (1952).
- (28) Simmons, W. F., and Cross, H. C., "The Elevated Temperature Properties of Chromium-Molybdenum Steels", ASTM-ASME Joint Committee, ASTM Special Publication No. 151 (1953).
- (29) Simmons, W. F., and Cross, H. C., "The Elevated Temperature Properties of Selected Super-Strength Alloys", ASTM-ASME Joint Committee, ASTM Special Publication No. 160 (1954).
- (30) "Product Data Bulletin", Armoo Steel Corporation, Development Engineering Dept., Middletown, Ohio (1952).
- (31) Larson, F. R., and Miller, J., "A Time-Temperature Relationship for Rupture and Creep Stresses", ASME Transactions, Vol 74, No. 5, July 1952, pages 765-775.
- (32) Graighead, C. M., Grube, K. P., Eastwood, L. W., and Lorig, G. H. (Battelle Memorial Institute), "The Effects of Temperature on the Mechanical Properties of Magnesium Alloys", Project Rand, Rand Corporation, R-146 (October, 1949).
- (33) Guarnieri, G. J., and Salvaggi, J., "Limiting High Temperature Creep and Rupture Stresses on Sheet Alloys for Jet Applications", Cornell Aeronautical Laboratory, T. M., Cal. -39 (Project Squid, USM-USAF) (September, 1951).
- (34) Flanigan, leasen, and Dorn (University of Californie), "Study of Forming Properties of Aluminum Alloy Sheet at Elevated Temperatures Part XII: Stress Rupture and Greep Tests", Wright-Patterson Air Force Base Report No. W185 (March, 1945), Report N. W215 (June, 1945).
- (35) Dorn, J. E., and Tiez, T. E. (University of California), "Creep and Stress-Rupture Investigations on Some Alumnium Alloy Sheet Metals" (November, 1947). (See Reference 36.)





design curve for tensile vield strength  $(F_{ty})$  of 19-4DL stainless steel (hot rolled) at elevated temperature Rof. 29, Data Sheet 22, FIGURE 164.



Trnsile athength (F<sub>L.</sub>) of 19-9dl stainless steel (forging) at elevated temperature Ref. 29, Data Sheet 19. FIGURE 163,


WASC TR 55-150 Pt 5







Tensile yield strength (F<sub>ty</sub>) of 19-1dl stainless steel (Fording) At elevated temperature Ref. 29, Data Sheet 19. FIGURE 165.


WADC TR SS-150 Pt 5




design curve for tensile yield strength  $(\mathbf{r}_{ty})$  of 19-9DL stainless steel (forging) at elevated temperature Ref. 29, Data Sheet 19. FIGURE 166.











Tensile yield strength ( $F_{1y}$ ) of 19-9DL stainless (iteel (hot rolled) at elevated temperature FIGURE 169.


Ref. 29, Deta Sheet 25.





DESIGN CURYE FOR TENSILE STRENGTH ( $F_{\rm ty}$ ) OF 19-9DL STABILESS STEEL (HOT ROLLED) AT ELE VATED TEMPERATURE Ref. 29, Data Shoet 25. FIGURE 170.




TENRILE STRENOTII (F<sub>R.</sub>) OF 19-9DL STAINLESS STERL (HOT-COLD WORKED) AT BLEVATED TEMPERATURE Ref. 29, Data Sheet 17. FIGURE 171.








Design curve for tensile strength ( $F_{\rm hl}$ ) of 19-9dl stainless steel (hot-cold worked) at elevated temperature Ref. 29, Data Sheet 16. FIGURE 114.



Tensile yield strength  $(\mathbf{F}_{\mathbf{ty}})$  of 19-9DL stainless steel (hot rolled) at elevated temperature Ref. 29, Data Sheet 23. FIGURE 175.

192



LESIGN CURVE FOR TENSILE YIELD STRENGTH (F<sub>ty</sub>) of 19-4DL STAINLESS STEEL (HOT ROLLED) AT ELEVATED TEMPERATURE Ref. 29, Data Shoot 23. TICURE 176.

## 19-9DX ALLOY (AMS-5536) (AMS-5539)

The 19-9DX alloy was developed in 1950 as a columbium-free version of 19-9DL because of the scarcity of columbium at that time. It was found that if the columbium were eliminated in favor of somewhat higher titanium and molybdenum content, an alloy resulted which had equivalent properties at a lower strategic index. The typical chemical composition of 19-9DX is given in Table 11.

TABLE 11. TYPICAL CHEMICAL
COMPOSITION OF
19-9DX HEATRESISTANT ALLOY
(AMS-5538) (AMS-5539)

Weight
Per Cent
0.30
1.25
0,55
9.00
19.00
1.50
1.25
0.60
Balance

The metallurgy of 19-9DX is similar to that of 19-9DL; 19-9DX is essentially austenitic. Alloy 19-9DX is usually used in the annealed or stress-relieved condition for temperatures below approximately 1300 F and in the solution-treated and aged condition above approximately 1300 F. Other conditions have found use in various applications. The minimum mechanical properties of 19-9DX in the annealed condition are given in Table 12; properties of 19-9DX in the stress-relieved condition are given in Table 13.

TABLE 12. MINIMUM MECHANICAL PROPERTIES OF 19-9DX ALLOY (AMS-5538)

Property	
Ultimate tensile (Ftu)	95, 000-120, 000 pai
Innsile yield (Fty)	45, 000 psi (minimum)
Elongation (e) in 2 inches	30 per cent (mini- m)


TABLE 13. MINIMUM MECHANICAL PROPERTIES OF 19-9DX ALLOY (AMS-5539)


Property	
Ultimate tensile (Ftu)	125, 000 psi (minimum)
Tensile yield (Fty)	90,000 psi (minimum)
Elongation (e) in 2 inches	12 per cezt (minimum)

The short-time, elevated-temperature properties of 19-9DX are shown in the following curves:


- (1) Tensile properties, Figures 177 through 162 and 189 through 194
- (2) Compressive properties, Figures 183, 184, 195, and
- (3) Bearing properties, Figures 185 through 158 and 197 through 197.

Stress-strain curves and data on shear strength and modulus are lacking for 19-90X.






THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF




Design curve for tensile strength (F<sub>to</sub>) of 19-9dx (AMS-5534) Etainless steel at elevated temperature FIGURE 179.

WADC TR 55-150 Pt \$




Tensile tield strencth (f<sub>t</sub>) of 19-9dx (ams-5538) stanless steel at elevated temperature FIGURE 180.

CONTRACTOR TOWN



Tenbile tield btrength (f<sub>ty</sub>) expressed ab a percentage of room-temperature tensile yield btrength of 19-9dx (amb-5518) stain-less bteel at elevated temperature FIGURE 181.

WADC TR 55-150 Pt 5



Wade triss-150 in 5






Figure 181. Compressive tield btrength  $(r_{\rm cv})$  of 19-4dx (ams-8834) stanless ether at elevated temperature Raf. 107.


WADC TR SS-150 Pt 5



design curit for compressive yield strength  $(F_{c\gamma})$  of 19-9dx (AMS-5538) stainless steel at elevated temperature Ref. 207. FIGURE 184.




DEARING STRENGTII (F. D. OF 19-9DX (AMS-9938) STAINLESS STEEL. AT ELEVATED TEMPERATURE Ref. 207 FIGURE 185.




DESIGN CURVE FOR BEARING STRENGTH (F<sub>bru</sub>) of 19-9DX (AMS-5538) STAINLESS STEEL AT ELEVATED TEMPERATURE FIGURE 186.

Ref. 201.


**405** 




Bearing Yield Strength (F<sub>bry</sub>) of 19-50x (Ams-8938) Stainling Sterl at Elevated Temperatura Rof. 207. FIGURE 187,





WADC TR SS-LS# FE S




Tensile strength ( $\mathbf{r}_{tv}$ ) of 19-9dx (also-5539) stainless stree at elevated temperature Ref. 107, 241. FIGURE 189.







Design curve for tensile strength ( $\mathbf{r}_{\mathbf{t}_0}$ ) of 19-9dx (AMS-8339) stainless steel at elevated temperature FIGURE 191.




Tensile yield strength ( $\mathbf{r}_{ty}$ ) of 19-9dx (AMS-1939) stainless stell at elevated temperature FIGURE 192.

Rof. 207, 241.


WADC TR 55-150 Pt 5


યા



TENSILE YIELD STRENGTH (F<sub>ty</sub>) EXPRESSED AS A PERCENTAGE OF ROOM-TEMPERATURE TENSILE YIELD STRENGTH OF 19-9DX (AMS-5539) STAIN-LESS STEEL AT ELEVATED TEMPERATURE FIGURE 193.

WASC OX TI-150 Pt 5






の間のなべなかられる目にはいくとして

COMPRESSIVE TIELD STRENGTH (F., OF 19-9DX (AMS-5539) STAINLESS STEEL AT ELEVATED TEMPERATURE Ref. 207. FIGURE 195.

14

TADC TE SS-150 Pt 5



deskin curve for compressive tield strength ( $r_{\rm cy}$ ) of 19-9dx (ams-5539) stainless steel at elevated temperature Ref. 207. PICURE 196.







FIGURE 197. BEARING STRENGTH (F<sub>bru</sub>) of 19-9DX (AMS-5539) STAINLESS STEEL AT Elevated temperature





Bearing Yield Strength (F<sub>bry</sub>) of 19-9DX (AMS-5519) stainless Steel at Elevated Temperature FIGURE 197.



Design curve for bearing yield strength (F<sub>bry</sub>) of 19-9DX (AMS-5539) stainless strel at elevated temperature FIGURE 200.

## A-286 ALLOY

The A-286 is an austenitic alloy which has been made heat treatable by the addition of titanium. The typical chemical composition of A-286 is shown in Table 14.

TABLE 14. TYPICAL CHEMICAL COMPOSITION OF A-266 ALLOY


Element	Weight Per Cent
Manganese	1, 35
Silicon	. 0.95
Nickel	26.00
Chromium	15.50
Molybdenum	1.25
Titanium	1.95
Vanadium	0.32
Aluminum ,	0.20
Iron	Balance

Alloy A-286 is a precipitation-hardening alloy that develops its optimum properties by solution treating at 1800 F, followed by rapid cooling (oil quenching for large sections and air cooling for thin sections, such as sheet), and finally aging at 1325 F for a minimum time of 12 hours. The aging treatment develops the strength of A-286 by random formation of a fine precipitate in the austenitic matrix.


The short-time, elevated-temperature properties of A-286 are shown in the following curves:

- (1) Teasile properties, Figures 201 through 204
- (2) Modulus of elasticity, Figures 205 and 207
- (3) Poisson's ratio, Figure 206
- (4) Stress-strain curves, Figure 208

No compressive, shear, or bearing data were available on A-286.



Tensile strength ( $\mathbf{F}_{\mathbf{tu}}$ ) of A-286 alloy at elevated temperature FIGURE 201.



debign curve for tensile 5 "thc ii ( $\mathbb{F}_{tu}$ ) of -.286 alloy at elevated temperatibe FIGURE 202.

Ref. 29, 76, 86, 207, 215.





FIGURE 203. TENSILE YIELD STRENGTH (F<sub>ty</sub>) OF A-286 ALLOY AT ELEVATED TEMPERATURE Ref. 29.






FIGURE 204. DESIGN CURVE FOR TENSILE YIELD STRENGTH (F<sub>ty</sub>) OF A-286 ALLOY AT ELEVATED TEMPERATURE Ref. 29.




FIGURE 205. EFFECT OF ELEVATED TEMPERATURE ON THE MODULUS OF RIGIDITY (G) OF A-286 ALLOY





Figure 206. Effect of elevated temperature on poisson's ratio (4) of A-286 alloy



THE ACTION AND A COMPANY OF A STATE OF A STATE AND A STATE OF A ST

これのののの一種ならなからのの時間できたのです。

WADC TR 55-150 Pt 5

FIGURE 207. TENSILE MODULUS (E) OF A-286 ALLOY (SHEET) AT ELEVATED TEMPERATURE

Ref. 207, p 9-3-1-1.




FIGURE 208. TENSILE STRESS-STRAIN CURVES FOR A- 286 ALLOY SHEET

Ref. 207.

## INCONEL =X= (MIL-N-7786) (AMS-5542D)

Income! "X" is a wrought nickel-bale alloy which is highly resistant to chemical corrosion and oxidation. Additions of titalium and aluminum render the alloy age-hardenable. The limiting chemical composition of income! "X" is given in Table 15.

TABLE 15. CHEMICAL COMPOSITION OF INCONEL "Y" (MIL-N-7786) (AMS-5542D)

	Weight Per Cent
Element	
Nickel, minimum	70.0
Chromium	14-16
Iron	5-9
Titanium	2.25-2.75
Columbium + tantalum	0.7-1.2
Aluminum	0.4-1.0
Silicon, maximum	0.5
Manganese	0.3-1.0
Copper, maximum	0.2
Carbon, maximum	0.08
Sulfur, maximum	0.01

Two typical conditions for hot-rolled Inconel "X" are summarized below.

## Fully Heat-Treated Hot-Rolled Rods

- (a) Solution treated at 2100 F for 4 hours and air-cooled
- (b) Aged at 1550 F for 24 hours and mir cooled
- (c) Aged at 1300 F for 20 hours and air cooled.

Typical room-temperature properties for this condition are shown in Table 16.

TABLE 16. TYPICAL ROOM-TEMPERATURE
PROPERTIES OF FULLY HEATTREATED HOT-ROLLED
INCONEL "X"

Property	
Ultimate tensile (Ftu)	162, 000 psi
Tensile yield (Fty)	92,000 psi
Elongation (e) in 2 inches	24 per cent
Reduction in area	30 per cent

## Hot Rolled and Aged, Not Sulution Treated

(a) Aged at 1300 F for 20 hours.

I p. cel room-temperature properties for this condition are shown in Table 17.

TABLE 17. TYPICAL ROOM-TEMPERATURE PROPERTIES OF HOT-ROLLED AND AGED INCONEL \*\*X\*\*

Property	
Ultimate tensile (Ftu)	184, 000 psi
Tensile yield (Fty)	132,000 psi
Elongation (e) in 2 inches	24 per cent
Reduction in area	37 per cent

Note: All high-temperature heat treating must be done in a suffuriree atmosphere.

Minimum mechanical properties of Incomel "X" as specified in AMS-5542D are given in Table 18.


TABLE 18. MINIMUM MECHANICAL PROPERTIES OF INCONEL "X" (AMS-5542D)

Property	
Ultimate tensile (Ftu)	155,000 psi
Tensile yield (Fty)	100,000 psi
Elmeation (e) in 2 inches	20 per cent


The short-time elevated-temperature properties of Incomel "X" are shown in the following curves:


- (1) Tensile properties, Figures 209 through 215
- (2) Compressive properties, Figures 216 and 217
- (3) Bearing properties, Figures 218 through 220
- (4) Shear properties, Figures 221 through 224
- (5) Modulus of elasticity, Figures 225 and 227
- (6) Poisson's ratio, Figure 226
- (7) Stress-strain curves, Figures 228 through 230

Data are available on incomel "X" for all surveyed properties,



Tensile and tensile yield strengths ( $\mathbf{F}_{1u}$  and  $\mathbf{F}_{1y}$ ) of inconel "K" at elevated temperature FIGURE 209.





Tensile and tensile yield strengths ( $F_{i,u}$  and  $F_{i,y}$ ) of inconel "X" at elevated temperature FIGURE 211.

WADC TA SS-150 Pt 5




Figure 112. Effect of strain rate on the tensile strength ( $\mathbf{r}_{i\omega}$ ) of inconel "x" at elevated temperature Ref. WADC 55-199, Part 2, p 46.




Figure 213. Effect of strain rate on the tensile yield strength  $(F_{ty})$  of inconel "X" at elevated temperature Ref. WADC 55-199, Part 2, p 46.




figure 214. Design curve for tensile btrength ( $\mathbf{r}_{\mathbf{n}_{i}}$ ) of disconel "X" at elevated temperature




Figure 215. Design curve for tensile yield strength  $(\mathbf{F}_{ty})$  of dyconel "X" at elevated temperature




Figure 216. Compressive yield strength (F<sub>by</sub>) of inconel "X" At relevated temperature

WADC TR 55-150 Pt 5





figure 217. Design curve for compressive yield strength ( $r_{\rm dy}$ ) of inconel . "X" at elevated temperature

WADCITE 55-150 Pt \$



bearing and bearing yield strength (f<sub>bru</sub>and f<sub>bry</sub>) of inconel "X" at elevated temperature FIGURE 218.






FIGURE 119. DESIGN CURVE FOR BEARING STRENGTH (Fbru) OF INCONEL "X" AT PILEVATED TEMPERATURE



WADC TR 55-150 Pt 5



design curve for bearing yield strength (f<sub>bry</sub>) of inconel "X" at elevated temperature FIGURE 220.




FIGURE 221. BHEAR STRENGTH (F<sub>BU</sub>) OF INCONEL "X" AT ELEVATED TEMPERATURE

344

WADC TR SS-150 PLS






FIGURE 212. DESIGN CURVE FOR SHEAR STRENGTH (F<sub>BU</sub>) OF INCONEL "X" AT ELEVATED TEMPERATURE




WADC TR 55-150 Pr 5




Pigure 113. Shear Strength (F<sub>eu</sub>) of diconfl "X" at Eleva? Ed Temperature

Rof. 177.


WADC TR 55-150 Pt 5





247

WADC TR 55-150 Pt 5



Tenbile and compressive moduli (e and  $\mathbf{e}_{c}$ ) of inconel "x" at elevated temperature Ref. 207. FIGURE 227.





FIGURE 224. TENSILE STRESS-STRAIN CURVES FOR INCONEL.
"Y" AT ROOM AND ELEVATED TEMPERATURE

MCL-N-7786A (ASC) Base 2011, p 9-2-8-8. Walder vir eshedish pr 5 251






FIGURE 229. COMPRESSIVE STRESS-STRAIN CURVES FOR INCONEL "X" AT ROOM AND ELEVATED TEMPERATURE

MIL-N-7786A (ASG)

Ref. 207, p 9-2-7-2.

WADC TR 55-150 Pt 5 252




FIGURE 230. TENSILE STRESS-STRAIN CURVE FOR INCONEL "X" AT ROOM TEMPERATURE

Ref. 207, 1-9-2-7.

WALDC TR 55-150 Pt 5

න

## STAINLESS "W" ALLOY

Stainless "W" is a ferritic-type stainless steel. Because of additions of titanium and aluminum, the steel responds to a precipitation-hardening heat treatment for increased strength and hardness. The nominal composition of Stainless "W" is shown in Table 19.

TABLE 19. NOMINAL CHEMICAL COMPOSITION OF STAINLESS "W" ALLOY


Element	Weight Per Cent
Carbon	0, 07
Manganese	0,50
Silicon	0,50
Nickel	7,00
Chromium	17.00
Titanium	0, 70
Aluminum	0.20
Iron	Eniance

Heat-treating procedures are summarized as follows: (1) to solution anneal, air cool from temperatures within the range of 1200 to 2000 F (usually 1850 to 1950 F for 15 to 30 minutes); (2) to precipitation harden, heat to a temperature of 800 to 1200 F and water quench or air cool. Ultimate mechanical properties depend on holding time and temperature of precipitation hardening. Water quenching from the aging temperature produces higher strength properties.

The short-time, elevated-temperature properties of Stainless www are shown in the following curves:

- (1) Tensile properties, Figures 231 through 234.
- (2) Poisson's ratio, Figure 235.
- (3) Modulus of elasticity, Figure 236.
- (4) Stress-strain curves, Figures 237 through 240.


Shear, bearing, and compressive properties and stress-strain curves at elevated temperature are lacking for Stainless "W" alloy.



TENSILE STRENGTH (F<sub>14</sub>) OF STAINLESS "W" ALLOY AT ELEVATED TEMPERATURE FIGURE 231.

Ref. 358.

WADC TR 55-856 Pt 5



DESIGN CURVE FOR TENSILE STRENGTH ( $\mathbf{F_{tu}}$ ) of Stainless "W" alloy at elevated temperature FIGURE 232.

Ref. 358.

VACC TR 55-690 PL 5

25%





FIGURE 233. TENSILE YEELD STRENGTH (F<sub>ty</sub>) OF STAINLESS "W" ALLOY AT ELEVATED TEMPERATURE Ref. 358.

WADC TR 55-150 Pt 5






Figure 235. Effect of elevated temperature on poisson's ratio ( $\mu$ ) of stainless "W" alloy

Rof. 356.

WADC TR 55-150 Pt 5

**25%** 




FIGURE 236. TENSILE MODULUS (E) OF STAINLESS "W" ALLOY AT
, ELEVATED TEMPERATURE
Ref. 358.

WALK TR 55-250 Pt 5

264

**,** 




FIGURE 237. TENSILE STRESS-STRAIN CHEME FOR STANCLESS
THE ALLOY AT ROOM TEMPERATURE
(LONGITUDINAL PROPERTY)

Ref. 358, WADC TR 55-150 Pt 5




FIGURE 238. TENSILE STPESS-STRAIN CUEVE FOR STAINLESS
"#" ALLOY AT ROOM TEMPERATURE
(TRANSVERSE PROPERTY)

Ref. 158, WAD C TR 55-150 Pt 5




FIGURE APP. ADDITIONAL STREET STREET CURVE FOR STAINLESS "W" ALLOY AT ROOM TEMPERATURE (LONGITUDINAL PROPERTY)

Re'. 385.

WADC TR 55-150 Pt 5




FIGURE 24). COMPRESSIVE STRESS-STRAIN CURVE FOR STAINLESS
"Y" ALLOY AT ROOM TEMPERATURE (TRANSVERSE
PROPERTY)


Ref. 385, WADC TR 55-150 Pt 5


# APPENDIX I

# MATERIAL COMPARISON CURVES

For convenience, the following curves have been plotted to show the relative strengths of the various alloys discussed in this report.


	Page	
Figure 241.	Comparison of Tensile Strengths (Ftu) of Stainless Sicels and Super Alloys at Elevated Temperature 266	
Figure 242.	Comparison of Tensile Strengths (Fti) of Precipitation Hardenable Stainless Steels at Elevated Temperature 267	
Figure 243,	Comparison of Tensile Strengths (Ftu) of AM-350 Stainless Steel at Elevated Temperature	
Figure 244.	Comparison of Tensile Strength Ftu) of 19-9DL Stain- less Steel at Elevated Tens crature	
Figure 245.	Comparison of Compressive Yield Strengths (F <sub>cy</sub> ) of Stainless Steels and Super Alloys at Elevated Temperature	
Figure 246.	Comparison of Bearing Strengths (F <sub>bru</sub> ) of Stainless Strels at Elevated Temperature	
Figure 247.	Comparison of Shear Strengths (F <sub>su</sub> ) of Stainless Steels	





COMPARISON OF TENSILE STRENGTHS (F<sub>IL</sub>) OF STAINLESS STEELS AND SUPER ALLOYS AT ELEVATED TEMPERATURE FIGURE 241.

WALC TR 55-150 Pt 5







FIGURE 243. COMPARISON OF TENSILE STRENGTHS (F<sub>tu</sub>) of AM-350 STAINLESS STEEL At Elevated Temperature

WADC TR 55-150 Pt 5

26#



COMPARISON OF TENSILE STRENGTHB (F<sub>tu</sub>) of 19-9DL STAINLESS STEEL AT ELEVATED TEMPERATURE FIGURE 244.





Figure 245. Comparison of compressive yield strengtiss  $\{r_{o,y}\}$  of stainless stells and super alloys at elevated temperature



ションション 動き アインストンは 魔で ディア・アンプログ

Figure 246. Comparison of Bearing strengths ( $\mathbf{F}_{b_{7}u}$ ) of stainless steels at elevated temperature

ZTX




FIGURE 247. COMPARISON OF SHEAR STRENGTHS (Fou) OF STAINLESS STEELS AT ELEVATED TEMPERATURE

が<br />
と<br />
の<br />
と<br />
の<br />
と<br />
の<br />
と<br />
の<br />
の<br

#### APPENDIX II

### BIBLIOGRAPHY

- (1) Clark, F. H.: Metals at High Temperature, Reinkold, New York (1950), 372 pages.
- (2) "Stainless and Heat-Resisting Steels", Steel Products Manual Section 24, AlSI (February, 1949), 142 pages.
- (3) Franks, R., and Binder, W. O., "Tension and Compression Stress-Strain Characteristics of Cold-Rolled Austentic Chromium-Nickel and Chromium-Manganese-Nickel Stainless Steels", Journal of the Aeronautical Sciences, Vol 9, 1941-1942, pages 419-436.
- (4) Data compiled by the Subcommittee on Wrought Heat-Resisting Alloys at the American Society for Metals, Cleveland, Ohio.
- (5) Franks, Russell, and LaQue, Francis L., "Data on Chemical Composition, Physical and Mechanical Properties of Wonght Corrosion Resisting and Heat-Evaluating Chromium-Nickel Steels", ASTM Committee A-10 on Iron-Chromium, Iron-Chromium-Nickel, and Related Alloys, 1942, 43 pages.
- (6) "Steels for Elevated Temperature Service", United States Steel Corporation, 1942, 87 pages.
- (7) Franks, R., Juppenlatz, J. W., Krivobok, V. N., LaQue, F. L., Peters, F. P., and Schoefer, E. A., "Data on Corrosion and Heat-Resisting Steels and Alloys Wrought and Crst", ASTM Committee A-10 Report, Special Technical Publication 52A, May 1950, 79 pages.
- (8) Metals Handbook, Edited by T. Lyman, 1948 Edition, American Society for Metals, Cleveland (1948), 1444 pages.
- (9) "Stainless Croloys", Babcock and Wilcox Company, Technical Bulletin 1B (1951), Beaver Falls, Pa.
- (10) "Alloy Digest", Engineering Alloys Digest, Inc., Upper Mountclair, New Jersey, 1953-1957.
- (11) Simmons, Ward F., et al., "Compiletion of Compositions and Strengths of Super-Strength Alloys", ASTM Special Technical Publication No. 170 (1955).

- (12) "Republic Enduro Stainless Steels", Republic Steel Corporation, Cleveland (1951).
- (13) Thum, E. E., Book of Stainless Steels, American Society for Metals, Cleveland (1935).
- (14) "Working Data for Stainless and Heat Resisting Steels", Carpenter Steel Company (1952), Reading, Pa.
- (15) Miller, R. P., and Herger, J. J., "The Strength of Wrought Steels at Elevated Temperature", ASTM STP 100 (March, 1950). Same as Reference 26.
- (16) Seager, M. H., and Nortcliffe, J., "Influence of Temperature on Modulus of Elasticity of Plain Carbon and Alloy Steels", Journal of the Iron and Steel Institute (London), Vol 147, 1943, pages 103P-119P.
- (17) Roberts, M. H., and Nortcuffe, J., "Measurements of Young's Modulus at High Temperatures", Journal of the Iron and Steel Institute (London), Vol 157, Part 3, November 1947, pages 345-348.
- (18) Metals Handbook Supplement, American Society for Metals, Cleveland (July 15, 1954).
- (19) Scott, H., and Gordon, R. B., "Precipitation Hardened Alloys for Gas Turbine Service, II", ASME Transactions, Vol 60, 1947, pages 583-593.
- (20) "Structural Development Note No. 17, Elevated Temperature Design Criteria - Structural Metals and Alloys", Boeing Airplane Company, Report No. D-14715, Seattle (December 4, 1954).
- (21) Cross, H. C., and Simmons, W. F., "Heat-Resisting Metals for Gas Turbine Parts", ASTM Symposium on Materials for Gas Turbines (June, 1946).
- (22) Freeman, J. W., Reynolds, E. E., and White, A. E., "High-Temperature Alloys Developed for Aircraft Turbosuperchargers and Gas Turbines", ASTM Symposium on Materials for Gas Turbines, pp 52-79, Disc. p. 121, Phil. (1946).
- (23) Grant, N. J., Frederickson, A. F., and Taylor, M. E., "Heat-Resistant Alloys From 1200 to 1800 Fn, Research Memo No. 3-47, Navships 250-330-12 (September 1, 1947).
- (24) Grant, N. J., Frederickson, A. F., and Taylor, M. E., "Heat-Resistant Alloys From 1200 to 1800 F", Iron Age, Vol 161, March 18, pages 73-78, April 8, pages 75-81, and April 15, 1948, pages 84-93.

- (36) Craughesd, C. M., Eastwood, L. W., and Lorig, C. H. (Battelle Memorial Institute), "An Appraisal of the Usefulness of Aluminum Alloys io: Supersonic Aircraft and Guided Missile Construction", Project Rand, Report No. R 164 (August, 1948).
- (37) Preston, D., "Exploratory Investigation of High Temperature Sheet Materials", American Society for Testing Materials, Proceedings, Vol. 52, 1952, pages 962-966.
- (35) Guarmeri, Yerkovitch (Cornell Aermauticai Labs), "Jet Engine Materials", Progress Report No. KB-511-M-3, WADC Contract No. AF 33(616)-42.
- (39) Trapp, W. J., "Elevated Temperature Fatigue Properties of SAE 4340 Steel", WADC TR 52-325, 50 pages (December, 1952).
- (40) Newman, Fones, and Brown, "Time-Temperature Dependence of the Notch Effect and Influence of Notch Depth in Stress Rupture Tests on Cr-Mo-V Steel", American Society for Testing Materials, Vol 53, 1953, pages 677-692.
- (41) Miller, J., "Aid for High Temperature Designer", General Electric Corporation Review, Vol 55, November 1952, pages 51-53,
- (42) Freeman, Rote, and White (University of Michigan), "High Temperature Characteristics of 17 Alloys at 1200 and 1350 Ft, Allegheny Ladium Steel Corporation Technical Data on A-286,
- (43) Freeman, J. W., Rote, F. B., and White, A. E., "High-Temperature Characteristics of 17 Alloys at 1200 and 1350 F", NACA, ARC No. 4022 (March, 1944).
- (44) "Dymposium on Materials for Gas Turbines", American Society for Testing Materials (1946).
- (45) Lazan, B. J., and Westberg, E. (Syracuse University), "Properties of Temperature Resistant Materials Under Tensile and Compressive Fabrue Stresses", WADC TR 52-227 (November, 1952).
- (46) "Physical Constants of Some Commercial Steels" (British Standard EN Steels), Physics Division, National Physical Laboratory for Thermal Treatment Subcommittee of the Iron and Steel Institute (British), Butterworth Scientific Publications, London (1953).
- 147) Giark, C. L., "American Developments in Alloys for High Temperatures", Metal Progress, ASM, Vol 65, No. 1, Januar, 1974, pages 72-76.

- (48) Cross, M. C., McMaster, R. C., Simmons, W. F., and VanEcho, J. A., "Short-Time, High-Temperature Properties of Heat-Resisting Alloy Sheet", (Banelle Memorial Institute), Project Rand (February 27, 1948).
- (49) Simmons, W. F., VanEcho, J. A., and Cross, H. C., "Short-Time, High-Temperature Properties of Heat-Resisting Alloy Sheet" (Battelle Memorial Institute), Project Rand (December '5, 1948).
- (50) VanEcho, J., Page, L. C., Simmons, W. F., and Cross, H. C. (Battelle Memorial Institute). "Short-Time Creep Properties of Structural Secet Materials for Aircraft and Missiles", USAF-ATSC Technical Report No. 6731, Part I (August, 1952).
- (51) VanEcho, J. A., Simmons, W. F., and Cross, H. C. (Battelie Memorial Institute), "Short-Time Creep Properties of Structural Sheet Materials for Aircraft and Missiles", USAF-ASTC Technical Report No. 6731, Part II (January, 1953).
- (52) VanEcho, J. A., Sammons, W. F., and Cross, H. G. (Battelle Memorial Institute), "Short-Time Greep Properties of Structural Sheet Materials for Aircraft and Missiles", USAF-ASTC Technical Report No. 6731, Part III (October, 1954).
- (53) Clauser, H. R., "Materials for High Temperature Service", Materials and Methods, Vol 37, April 1954, pages 117-132.
- (54) Woldman, N. E., Enrineering Alloys, American Society for Metals, Cleveland (1954).
- (55) "Standardization H-IA Supply and Logistics Handbook", U. S. Department of Defense, Office of the Assistant Secretary, Washington, D. C. (April 8, 1954).
- (56) Doerr, D. D., "Determination of Physical Properties of Ferrous and Nonferrous Structurel Sneet Materials at Elevated Temperatures", Armour Research Foundation, AF Technical Report No. 6517, Part I, WADC-ARDC (December, 1951).
- (57) Poerr, D. D., "Determination of Physical Properties of Ferrous and Nonferrous Structural Sheet Materials at Elevated Temperatures", Armour Research Foundation, AF Technical Report No. 6517, Part II, WADC-ARDC (April, 1954).
- (13) Miller, D. E., "Determination of Physical Properties of Ferrous and Nonfe rous Structural Sheet Materials at Elevated Temperatures", Armour Research Foundation, AS Technical Report No. 6517, Part III (June, 1994).

- (59) Doerr, D. D., "Determination of Physical Properties of Ferrous and Nonterrous Structural Sheet Materials at Elevated Temperatures", Armour Research Foundation, Progress Report No. 47 (January 13, 1954).
- (60) Doerr, D. D., "Determination of Physical Properties of Ferrous and Nonierrous Structural Spect Materials at Elevated Temperatures", Armour Research Foundation, Progress Report No. 48 (February 8, 1954).
- (61) Doerr, D. D., "Determination of Physical Properties of Ferrous and Nonierrous Structural Sheet Materials at Elevated Temperatures", Armour Research Foundation, Progress Report No. 49 (March 9, 1954).
- (62) Doerr, D. D. "Determination of Physical Properties of Ferrous and Nonterrous Structural Sheet Materials at Elevated Temperatures", Armour Research Foundation, Progress Report No. 50 (May 3, 1954).
- (63) Doerr, D. D., "Determination of Physical Properties of Ferrous and Nonferrous Structural Sheet Materials at Elevated Temperatures", Armour Research Foundation, Progress Report No. 51 (May 18, 1954).
- (64) Doerr, D. D., "Determination of Physical Properties of Ferrous and Nonferrous Structural Sheet Materials at Elevated Temperatures", Armour Research Foundation, Progress Report No. 52 (June 8, 1954).
- (65) Doerr, D. D., "Determination of Physical Properties of Ferrous and Nonferrous Structural Sheet Materials at Elevated Temperatures", Armour Research Foundation, Progress Report No. 53 (July 19, 1954).
- (66) Doerr, D. D., "Determination of Physical Properties of Ferrous and Nonferrous Structural Sheet Materials at Elevated Temperatures", Armour Research Foundation, Progress Report No. 54 (August 25, 1954).
- (67) Doerr, D. D., "Determination of Physical Properties of Ferrous and Nonferrous Structural Sheet Materials at Elevated Temperatures", Armour Research Foundation, Progress Report No. 55 (September 24, 1954).
- (68) Doerr, D. D., "Determination of Physical Properties of Ferrous and Nonferrous Structural Sheet Materials at Elevated Temperatures", Armour Research Foundation, Progress Report No. 56 (November 1, 1954).
- (69) G. rdon, S. A., Simon, R., and Achbach, W. P., "Elastic Moduli: Thrir Determination and Limits of Application", WADC TR 55-150, Part 4 (August, 1956).

- (70) Freeman, J. S., and Rush, A. I., "Statistical Evaluation of the Greep-Rupture Properties of Four Heat-Resistant Alloys in Shee: Form", Aviation Panel of the ASME-ASTM Joint Committee on the Effect of Temperature of the Properties of Metals (June 1, 1954).
- (71) Doerr, D., "Determination of Physical Properties of Nonferrous Structural Sheet Materials at Elevated Temperatures", Armour Research Foundation, AF Technical Report No. 6517, Part 1, Supplement I., WADC-ARDC (February, 1953).
- (72) Babcock and Wilcox, Technical Bulletin No. E19, Mechanical and Physical Properties of High Temperature Tube Materials (1954).
- (73) "Medium Carbon Pearlite Alloy Steels for High Temperature Applications", Technical Bulletin Number 36A, Timken (1953).
- (74) "Materials-Property-Design Criteria for Metals", WADC Technical Report 55-150, Part I (December, 1954).
- (75) "Stainless and Heat Resisting Steels", Steel Products Manual, Section 24, AISI (February, 1949).
- (76) Allegheny Ludlum Blue Sheets printed continuously, Allegheay Ludlum Steel Corporation, Brackenridge, Pa.
- (77) "Properties and Characteristics of 27 Per Cent Chromium-Iron",
  Bulletin TR-506, Reprinted from Metal Progress, Babcock and Wilcox
  Tube Co. (May. 1946).
- (78) "Armco Precipitation Hardening, Stainless Steels, Armco 17-7PH Sneet, Strip, and Plate", Armco Product Data Bulletin (March 1, 1954).
- (79) Armco Product Data Bulletin, Armco Steel Corporation, Middletown, Ohio (March 1, 1952).
- (80) "Armco Precipitation-Hardening Stainless Steels", Armco 17-4 PH
  Bar and Wire, Armco Product Data Bulletin, Armco Steel Corporation, Middletown, Ohio (March 1, 1954).
- (81) "Armco Precipitation-Hardening Stainless Steels", Armco 17-7 PH
  Bar and Wire, Armco Product Data Bulletin, Armco Steel Corporation, Middletown, Ohio (November 1, 1954).
- (82) "Armco Precipitation-Hardening Stainless Steels", Technical Data Manual, Armco 17-7 PH Sheets, Strip, and Plates, Armco Product Data Bulletin. Armco Steel Corporation, Middletown, Ohio (February 15, 1954).

- (63) "Felding Armoo 17-7 PH and 17-4 PH Precipitation-Hardening Stainless Steels", Armoo Fabricating Data Bulletin (November 1, 1954), Middletown, Obio.
- [64] "Arrico Precipitation Hardining Stainless Steels", Technical Data Marani, "Armico 17-4 PH, Bar, and Wire", Armico Product Data Ballena, Middletown, Ohio (no date).
- (65) Leza, Adolph J., "Alleghen, Metal 350 A New Type of Stainless Steel", Associate Director of Research, Allegheny Ludium Steel Corporation Research Laboratory, Brackenridge, Pennsylvania.
- (86) Lera, A. J., "Technical Data on Allegheny Ludlum Altoy A 286", Allegheny Ludlum Steel Corporation (1955).
- (57) Technical Data from General Electric Company, Air Gas Turbine Division, Evendale, Ohio.
- (86) "Haynes Alloys for High-Temperature Service", Haynes Stellite Company, Kokomo, Indiana (1950).
- (89) "Annealing Nickel, Monel, and inconel", Technical Bulletin T-20, International Nickel Company, Inc., revised (April, 1953).
- (90) "Hastelloy Alloy F, Haynes Alloys", Haynes Stellite Company, Kokomo, Indiana (March, 1953).
- (91) "Engineering Properties of K Monel and KR Monel", Technical Bulletin T-9, International Nickel Company, Inc., New York, revised (May, 1953).
- (92) \*Engineering Properties of Monel and R Monel\*, Technical Bulletin T-5, International Nickel Company, Inc., New York, revised (May, 1953).
- (93) Engineering Properties of Nickel<sup>10</sup>, Technical Bulletin T-15, International Nickel Company, Inc., New York, revised (July, 1949).
- (94) Betty, B. B., and Mudge, W. A., "Some Engineering Properties of Nickel and High-Nickel Alloys", Mechanical Engineering, Vol 67, February 1945, pages 123-129.
- (95) Woldman, N. E., "Nickel and High-Nickel Alloyen, Materials and Methods Manual &i, International Nickel Company, Inc., Vol 24, December 1946, pages 1475-1490.

- (96) LaQue, F. L., "Nickel and Nickel-Base Alloys", Technical Bulletin T-13, International Nickel Company, Inc., New York, revised (December, 1948).
- (97' "Index of Government and Engineering Society Specifications of Inco Nickel Alloys", International Nickel Company, Inc., 8th Edition (April 1, 1954).
- (98) "Engineering Properties of Inconel and Inconel "X", Technical Bulletin T-7, International Nickel Company, inc., New York (June, 1953).
- (99) Technical Data from International Nickel Company, Inc., New York.
- (100) Technical Data from Haynes Stellite Company, Kokomo, Indiana.
- (101) Howell, F. M., Aluminum Company of America Aluminum Research Laboratories, Unpublished, New Kennington, Pa.
- (102) Serby, O. D., Lietz, T. E., and Dorn, J. E., "The Greep Properties of Some Forged and Cast Aluminum Alloys", American Society for Testing Materials, Proceedings, Vol 51, 1951, pages 964-980.
- (103) Sherby, O. D., Dora, J. E., "Greep Properties of Two Tempers of 635 Extruded Aluminum Alloy", American Society for Testing Materials Proceedings, Vol 51, 1951, pages 945-953.
- (104) Sherby, O. D., and Dorn, J. E., "Effect of Annealing on the Cresp Properties of 2S-O Alloy", American Society for Testing Materials, Proceedings, Vol 51, 1951, pages 954-963.
- (105) Sherby, O. D., and Dorn, J. E., "The Creep Properties of Sand Cast Alaminum Materials 319-T71, 319-F, and 356T7", American Society for Testing Materials, Proceedings, Vol 52, 1952, pages 890-902.
- (106) Lyman, W. S., Pankaskie, P. J., and Dorn, J. E., "The Greep Properties of Sand Cast Aluminum Materials, SSA-F, GS42A-F, and C4A-T8", Sexies No. 34, Issue No. 7 (June, 1951).
- (107) Pankastie, P. J., Robinson, A. J., and Dora, J. E., "Creep and Stress-Rupture Properties of Some Permanent-Mold Casting Alumi\_\_um Alloys", Series No. 34, Issue No. 8 (September, 1951).
- (108) Pankaskie, P. J., Robinson, A. T., and Dorn, J. E., "The Creep Properties of Aluminum Forging Materials CS41A-T6 and S6121A-T6", Series No. 34, Issue No. 9 (September, 1951).

- (109) Schwitter, G. M., "Triple Alloy Structural Tuhing", Iron Age, Vol 156, August 22, 1946, pages 46-49.
- (110) "Engineering Properties and Applications of Ni-Resist", The International Nickel Company, 4th Edition (1954) (3124-12-54-2926 A-71).
- (111) Information obtained by personal visit by William Achbach of Battelle Memorial Institute to Boeing Airplane Co., Seattle, Wash. (1954-55).
- (112) "Engineering Properties and Applications of Ni-Hard", The International Nickel Company, Inc., 3rd Editors (20M 1954 2649).
- (113) Progress Report on Incoloy, International Nickel Co., Inc. (11M 10-53 2434), (October, 1953).
- (114) "Engineering Properties of Duranickel", Technical Bulletin, T-32, International Nickel Company, Inc. (February, 1955).
- (115) "The Present State of Development of Iron-Aluminum-Base Alloys", Titanium Metallurgical Laboratory, Bastelle Merson al Institute (November 25, 1955).
- (116) Nachman, J. F., and Buehler, W. J., "Thermond, A Non-Stramgic Aluminum, Iron Base Alloy for High Temperature Service", NavOrd Report 3700, June 25, 1954.
- (117) Hanink, D. K., Webbere, F. J., and Boezehold, A. L., "G. M. Research Labs Develop New Turbine Societ Alloy", SAE Journal, Vol 63, August 1755, pages 36-38.
- (118) "High Temperature Magnesium Extrusion Alloy", from Dow Chemical Company.
- (119) "HK31XA Sheet and Plate", fr.: "We Chemical Company, Midland, Michigan (May, 1955).
- (120) Guard, R. W., and Prater, T. A., "New Saper Alloy Speeds Jet Progress", The Iron Age, Vol 176, No. 16, October 20, 1955, pages 116-118.
- (121) Melcon, M. A., "Ultra High Strength Swel for Aircraft Structures", Product Engineering, Vol 24, October 1953, pages 129-141
- (122) "The Tensile and Impact Properties of Quenched and Tempered Nicke? Alloy Steels in Different Sizes", The International Nickel Company, Inc., New York, Copyright (1946), (331 1-55 2755 A-68).

- (123) "The Torsional and Shear Properties of Quenched and Tempered Nickel Alloy Steels in Different Sizes", International Nickel Company, Inc., New York (1M 10-54 2691 A-67), Copyright (1949).
- (124) Information obtained by personal visit to Universal-Cyclops Steel Corp., Bridgeville, Penn.
- (125) Krivobok, V. N., "Properties of Austenitic Stainless Steels at Low Temperatures", National Bureau of Standards Circular No. 520 (Mechanical Properties of Metals at Low Temperatures, 206 pages), 1952, pages 1-24.
- (126) "Some Properties of Low Carbon 8-1/2 Per Cent Nickel Steel", reprint of a paper presented at the National Conference on Petroleum Mechanical Engineering of the American Society of Mechanical Engineers, Huston, Texas, international Nickel Co., Inc., New York, Bulletin (October 5-8, 1947).
- (127) "Haynes Alloy '25' A Ductile Cobalt-Base Alloy for High Temperature Service", Haynes Stellite Co., Kokomo, Indiana (October 15, 1951).
- (128) Low, A. C., "The Effect of Mean Stress on the Fatigue Strength of Magnesium Alloy ZWS", Journal of the Royal Aeronautical Society, Vol 59, September 1955, pages 629-632.
- (129) "Fatigue Data Showing the Results of Tests on Top Joint Aluminum Panels", from Battelle Memorial Institute, unpublished.
- (130) Wuensch, Micheal E., President, Boro Marine and Industrial Corp., 1190 Per Cent Cupro-Nickel Alloy", Reprint from Marine News, The International Nickel Company, Inc. (February, 1955).
- (131) Bittner, E. T., "Alloy Spring Steels", American Society of Metals, Transactions, Vol 40, 1948, pages 263-280.
- (132) Loria, E. A., "Hot Work Die Steels for Aircraft Structures", Materials and Methods, Vol 42, No. 2, New York, pp 94-97 (August, 1955).
- (133) King, John E., "Cold Extrusion is Shaping Up", (Cold Forming Division, Heintz Mfg. Co.) (October 3, 1955).
- (134) Stainless Steel Handbook, Allegheny Ludlum Steel Corporation, Pittsburgh, 1951, 120 pages.
- (135) Progress Report No. 4 Contract No. AF 33(616)-2676 (September October, 1955).

- (136) Progress Report No. 3 Contract No. AF 33(616)-2876 (July-August, 1955).
- (137) "Structural Design Criteria for Titanium Alloya", Interim Report (August-October, 1954) Boeing Doc. D-14460-16-1, Boeing Airplane Co., Scattle, Wash, (Octobe, 27, 1954).
- (138) "Structural Design Criteria for Titanium Alloys", Boeing Contract
  No. AF 33(600)-23223, B-52, Interim Report (February, 1955-April,
  1955), (April 29, 1955), Boeing Airplane Co., Seattle, Wash.
- (139) "Structural Design Criteria for Titanium Alloys", Interim Report (November, 1954-January, 1955) Boeing Doc. D-14460-19-1, Boeing Airplane Co., Seattle, Wash. (January 31, 1955).
- (140) "Bend, Compression, Sheet Glassification and Tensile Data for Rem-Cru 6Al-4V and 4Al-4V Titanium Sheet at Room Temperature, 700°F and 900°F", Materials Research and Process Development Group, Rem-Cru Titanium, Midland, Pa.
- (141) Krivobok, V. N., and Talbot, A. M., "Effect of Temperatures on the Mechanical Properties, Characteristics, and Processing of Austenitic Stainless Steels", Proceedings of the American Society for Testing Materials, Vol 50, 1950, pages 895-930.
- (142) The Reactor Handbook, Vol 3, Sec. 1, Gent A Properties of Materials, U. S. Atomic Energy Commission, AECD 3647, March 1955.
- (143) Materials Research Reports NAA Received (October 31, 1955)
  MRR55-143 and MRR55-176, North American Aviation, Inc.,
  Englewood, California.
- (144) Hyler, W. S., "An Evaluation of Compression-Testing Techniques for Determining Elevated Temperature Properties of Titanium Sheet", Battelle Memorial Institute TML Report No. 43, June 8, 1954, 36 pages.
- (145) Gillig, Frank J., and Guarmieri, Glen J., "Study of The Tensile and Creep-Rupture Properties of Fifteen Heats of C-110M Titanium Alloy Sheet", Cornell Aeronautical Lab., Buifalo, N. Y. (September, 1955).
- (146) Simmons, W. F., and Cross, H. C., "Elevated-Temperature Properties of Carbon Steels", ASTM Special Technical Publication No. 180, American Society for Testing Materials, Philadelphia, September 1955.

- (147) Summary Report on "Engineering Properties of Heat-Resisting Allows", by Ward F. Simmons, C. W. Andrews, and Howard C. Cross, Battelle Memorial Institute, In cooperation with Office of Naval Research, Navy Department, Contract No. N5-ori-111 (November, 1947).
- (148) Muhlenbruch, C. W., Krivobok, V. N., and Mayne, C. R., "Mecham-cal Properties in Torsion and Polyagua Ratio for Certain Stainless Steel Alloys", American Society 104 Testing Materials, Proceedings, Vol 51, 1951, pages 932-856.
- (145) Carlson, MacDonald, and Simmons, "Factors Influencing the Match-Rupture Strength of Heat-Resistant Alloys at Elevated Temperatures", ASME paper No. 54-A-240 at Annual Heeting of Joint ASTM-/SME Committee (November 28, to December 3, 1954).
- (150) Schwitter, C. M., "Two New Gear histerials", Abstract of a Recent Paper Presented before the American Gear Manufacturers Association, Development and Research Division, International Nickel Co., Inc., New York.
- (151) Loria, E. A., "New Stainless Steels Qualify for High-Temperature Service", Lon Age, Vol 176, September 29, 1955, pages 65-67.
- [152] "Eigh Temperature Materials for High Speed Aircraft, Part I",
  Society of Automotive Engineers Joutnal, Vol 63, July, 1955, pages
  31-38.
- (153) "High Temperature Materials for High Speed Aircraft, Part II", Society of Automotive Engineers Journal, Vol 63, August 1955, pages 24-35.
- (154) "Heat Treating Gray Iron", Part 1, Steel, Vol 137, October 24, 1955, pages 118-122.
- (155) Sache, G., Sandahl, G. S., and Brown, W. F., Jr., "New Notes on High-Strength Heat-Treated Steels", Iron Age (November 23-30, 1955).
- (156) "Room and Elevated Temperature Progressian of Magnesium Sand Castings", Dow Chemical Co., Midland, Mich. (February 14, 1955).
- (157) "Heat Treatment and Physical Properties of the Austenitic Chromium-Nickel Stainless Steels", Copyright (1947) by the International Nickel Company, Inc., New York, N. Y.
- (158) "Crippling Strength of Magnesium Sheet and Extrusions", Technical Memorandum No. 15, Dow Chemical Ca., Midland, Mich.

- (159) Brusk, Robert S., Leman, Dreald, L., and Casey, John J., "The Properties of Some Magnesium-Lithum Alices Containing Alemanna and Zine", Dow Chemical Co., AIME Chicago sleeting (October, 1553).
- (160) Leontis, T. E., "Effect of feare-Earth Metris on the Properties of Extruded Magnesium", journal of Metals, Vol. 3, November 1951, pages 987-983.
- (161) "The Magazine of Magnesium", Brooks and Perkins Incorporated, Detroit to (August, 1955).
- (162) "Extruded and Rolled Products", Winte Metal Rolling and Stamming Corporation: Brooklyn, N. 7., 42 pages.
- (163) Schuette, Evan H., "Plastics and Work-Farriering Phenomena in Magnesium Alloys During Fixed-Redermon Fatigue Tests", Dow Chemical Co., Midland, Mach.
- (164) "Cast to Outlast", Bulletin by International Nickel Co., inc., 67 Wall Street, New York 5, N. Y.
- (165) Willard, J. R., and Cope, R. R. "Engineering With Aluminum", Modern Metals, Vol 11, September 1955.
- (166) "Foundry Facts", Modern Casturgs and American Foundrymen, voi 25, No. 3, September 1955, pages 69-79.
- (167) Levy, Alan V., "Application of High Temperature Materials to Air-craft Power Plants in the Temperature Range of 1200°F to 2400°F", presented to Aircraft Research Seminar (Secember 8, 1954).
- (168) Mayari, R., "Bethlehem's High Strength Corrosion Resisting Steel", Bethlehem Steel Co., (Bethlehem Steel Cataing No. 353), 1954, 64 pages.
- (164) Most, Norman S., "The Copper Alloy Forestry Co.", Reprist from Materials and Methods, Copper Alloy meierence Chart 1954 (1954).
- (170) Huffrian, James W., "Application of Metallic Materials for Aircrast Structures in the Temperature Range 660°F to 1100°F", presents. A Aircrast Research Seminar (December 8, 1954).
- (171) Davis, Charles S., "Thermal Laminations of Common Aircraft Materials", Presented at Aircraft Research Seminar (December 6, 1954).
- (172) Gurtis, L. W., "Open Flame Testing of Various Fiberglas Laminated Ducts at 2000"F", Presented at Aircraft Research Semman,

- (173) Gordon, S. A., "The Selection of Materials for High-Temperature Applications in Airframes", Battelie Memorial Institute TML Report No. 13, August 5, 1955, 22 pages.
- (174) Armstrong, T. N., and Brophy, G. R., "Some Properties of Low Carbon 5-1, 2 Per Cent Nickel Steel", Paper presented at the National Conference on Petroleum Mechanical Engineering of the ASME, Houston, Texas (October 5-8, 1947), 12 pages.
- (175) Boring, R. W., "Low Cost Alloys Offer Good Heat Resistance", Iron Age, Vol 173, No. 7, February 16, 1954, pages 137-141, Vol 173, No. 10, March 11, 1954, pages 146-148.
- (176) "Making the Most of Stainless Steels in the Chemical Process Industries", Bulletin by Crucible Steel Company of America, Pittsburgh, Pa.
- (177) "Physical Properties of Aircraft Structural Materials at Elevated Temperatures", Report No. 9112, Vol.1, by Chance Vought Aircraft, Dallas, Texas (June 1, 1955).
- (178) "Physical Properties of Aircraft Structural Materials at Elevated Temperatures", Report No. 9112, Vol. II, by Chance Yought Aircraft, Dallas, Texas (June 1, 1955).
- (179) "Sharon 430 Stainless Steel", Bulletin, Sharon Steel Corporation, Sharon, Pa.
- (180) "All Types of Stainless Steel Fastenings", Bulletin Star Stainless Screw Co., 655 Union Blvd., Paterson 2, New Jersey, Cat. No. 55A.
- (181) Data from Bulletin, Sharon Steel Company, Sharon, Pa.
- (162) Fruman, D. E., "Thermal Expansion Characteristics of Stainless Sieels Between 300" and 1000"F", AIME Transactions, Vol 188, No. 4, April, 1950, pages 688-691.
- (183) Titanium Metallurgical Laboratory Report No. 13, Battelle Memorial Institute (August, 1955).
- (164) "Lead Treated Steels", Bulletin from Copperweld Steel Co., Warren, Ohio.
- (185) "A Handbook on Monel, Nickel, Incomel, and Nickel Clad Copper in Form of Rod, Wire, and Strip", Bulletin, Alloy Metal Wire Company, Prospect Park, Fa.
- (15t) "Steel Casting Specifications Bulletin (T-Loy 34)", Unit Cast Corp., Toledo, Ohio.

- (187) "Steel Casting Specification Switchin (T-Loy 42)", Unit Cast Corp., Toledo, Ohio.
- (188) Phillips, E. M., and Weymouth, J. R., "Stress Better in the J47", Based on paper "Jet Engine-Compressor Blades Hard or Soft?", Presented at SAE Annual Meeting (January 12. 1955).
- (189) Kearns, W. H., Hyler, W. S., and Markin, D. C., "The Static and Fatigue Behavior of Spot-Welded Joints in Titanium", Welding Journal Research Supplement, May 1955, pages 241-250.
- (190) Kaufman, J. G., and D'Appolonia, E., "Torsion Prestrain and the Fatigue Strength of RC-55 Titanium Alloy", American Society for Testing Materials, Proceedings, Vol 55, 1955, pages 999-1014.
- (191) "Heat Resistant and Corrosion Resistant Alloy Castings in Industry", Bulletin by The International Nickel Company, Inc., New York.
- (192) Technical Data from North American Aviation, Inc., Los Angeles 45, California.
- (193) Rose, K., "Magnesium Casting Alloys for Elevated Temperatures", Materials and Methods, Vol 40, No. 1, July 1954, pages 87-89.
- (194) Hildebrand, J. F., and Strieter, F. P., "Mechanical Properties of Sand Cast Magnesium, Zinc, Zirconium Alloys", Dow Chemical Co., Midland, Mich.
- (195) Nelson, K. E., "Magnesium Sand Casting Alloys Containing Thorium", Dow Chemical Co., Midland, Mich.
- (196) Nelson, K. E., "Foundry Characteristics and Properties of the Magnesium Sand Casting Alloy HZ32XA", Dow Chemical Co., Midland, Mich.
- (197) Nelson, K. E., "Tensile and Creep Properties at Elevated Temperatures of Some Magnesium-Base Sand Casting Alloys", Dow Chemical Co., Midland, Mich.
- (198) "Crucible Rezistal Stainless Steel Selector", Chart by Crucible Steel Company of America, Copyright (1953), Pittsburgh, Pa.
- (199) Jackson, L. R., and Pochapsky, T. E., "The Effect of Composition of the Fatigue Strength of Decarburized Steel", Trans. ASM, Vol 39, pages 45-60.
- (200) "Stainless Fastners Stock List and Data Rook Catalogue Allmetal Screw", Products Co., Inc., Garden City, N. T.

- (201) The Aluminum Data Book, Reynolds Metals Company, 1954, 219 pages.
- (202) "Allegheny Metal Straight Chromium Grades as Alternate Selections for 18-8 Chromium-Nickel Stainless Steel", Bulletin-Allegiem Luslum Technical Studies, Number 1, by Allegheny Ludlum Steel Corporation,.
  Pittsburgh, Pa., Copyright (1952).
- (203) Alcoa Aluminum and Its Alloys, Aluminum Company of America.
  Pittaburgh, 1950.
- (204) Heat Treating A' aminum Alloys, Reynolds Metals Company, Comisville, 1948,
- (205) "Metal Progress", Reports of 19 Technical Committees of the American Society for Metals, Vol 68, Special Publication No. 2A, mignet 25, 1955.
- (206) Loria, E. A., "How Stainless Steels Rate for High Temperature",
  Pt. I, Iron Age, Vol 175, No. 14, April 7, 1955, pages 119-1177.
  "How Chromium Steels Rate for High Temperature Aircraft Secrets",
  Pt. II, Vol 175, No. 15, April 14, 1955, pages 103-106.
- (207) Material Property Data Sheets, North American Aviation, Inc., Les Angeles 45, Calif.
- (208) Sherman, R. G., and Kessler, H. D., "Ready Heat Treatable Titanium", Steel, Vol 137, No. 11, September 12, 1955, pages 92-100.
- (209) Luster, D. R., and Shakely, B. L., "How Titanium Alloys Britisher at High Temperature", Iron Age (March 24, 1955), Vol 175.
- (210) "Tentative Specifications for Metal-Arc Welded Steel Pipe ion High-Pressure Transmission Service", ASTM Publication, pp 213-218 (1954).
- (211) "haynes Alloys Hard Faring Manual", Haynes Stellite Co., Entermo, Ind. (December, 1954).
- (212) "Haynes Stellite Metal Cutting Tools", Haynes Stellite Bulletin, Haynes Stellite Co., Kokomo, Ind. (January, 1956).
- (213) Letner, H. R., "Residual Grinding Stresses in Hardened Samp", ASME fransactions, Vol 77, October 1955, pages 1089-1098.
- (214) Rosi, F. D., Perkins, F. C., and Alexander, B. H., "Mechanical Properties of Titanium", Third Quarterly Progress Report, Pare L. May 1 to August 1, 1951, Contract Number AF 33(038)-16031, Metallurgical Laboratories, Sylvania Electric Products, Inc., Bayside, N. Y.

- (215) Universal-Cyclops Steel Corporation, Bridgeville, Pa., Technical Data.
- (216) U. S. Steel Corporation, Pittsburgh, Pa., Technical Data.
- (217) Allegheny Ludlum Steel Corporation, Pittsburgh, Pa., Technical Data.
- (218) Pennington, W. J., and Richmond, F. M., "Comparison of Several Iron-Base High-Temperature Alloys", Compiled Data, Universal-Cyclops Steel Company, Bridgeville, Pennsylvania.
- (219) Universal-Cyclops Steel Corporation, Bridgeville, Pa., Technical Data, Loose Leaf (1956).
- (220) Barrett, Paul F., "Compressive Properties of Titanium Sheet at Elevated Temperatures", National Advisory Committee for Aeronautics, Technical Note 2038.
- (221) Boeing Airplane Company, Seattle, Wash., Data Sheets.
- (222) Battelle Memorial Institute, Compiled dat. (June, 1955).
- (223) McPhearson, D. J., "The Titanium Outlook", Modern Metals, Vol 11, January 1956.
- (224) Luster, D. R., and Shakely, B. L., "How Titanium Alloys Behave at High Temperatures", Iron Age, Vol 175, March 24, 1955, pages 96-99.
- (225) Brotsen, F. R., Harmon, H. L., Jr., and Troiano, A. R., "How Notch-Sensitive Are Titanium Alloys?", Iron Age, Vol 174, No. 27, December 30, 1954, pages 52-55.
- (226) Data Sheets from Rem-Gru Titanium Corporation, Midland, Pa.
- (227) Heimerl, G. J., and Hughes, P. J., "Structural Efficiencies of Various Aluminum, Titanium, and Steel Alloys at Elevated Temperatures", Tech Note 2975, National Advisory Committee for Aeronautics, July, 1953, pages 1-16.
- (228) Data Sheets from Convair, San Diego 12, California.
- (229) Dow, N. F., Hickman, W. A., and Rosen, B. W., "Data on the Compressive Strength of Skin Stringer Panels of Various Materials", NACA TN 1666, Washington, D. C., January 1954, pages 1-49.

- (230) Carpenter, S. R., "The Spotlight Turns to Titanium", A Lecture Presented on October 20, 1955, to the San Diego Chapter of the American Society for Metals.
- (231) Rem-Cru A-40, A-55, and A-70, Rem-Cru Titanium, Inc., Midland, Pennsylvania, Data Sheets.
- (232) Data from Crimible Steel Company of America, New York.
- (233) "Structural Design Criteria for Titanium Alloys", Interim Report, Contract No. AF 33/600)-23223, Boeing Airplane Company, Seattle, Wash, (Jun...y, 1954).
- (234) Technical Data from Haynes Stellite Company, Kokomo, Inc. (December 1, 1954).
- (235) American drake Shoe Company, Electro Alloys Division, Elyria, Ohio, Thermalloy 3 Distribution Pamphlet.
- (236) Hanink, D. K., Webbere, F. J., and Boegehold, A. L., "Development of a New Gas Turbine Superalloy GMR-235", Society of Automotive Engineers, Vol 63, 1955, pages 705-716.
- (237) Sticha, E. A. "Relaxation Behavior of Titanium Alloys", Third Quarterly Report, Contract No. AZ 33(616)-2400, Crane Company, Chicago, Illinois (January, 1955).
- (238) Cross, Howard C., and Simmons, Ward F., "Alloys and Their Froperties for Elevated Temperature Service", Symposium at the University of Michigan (March 11 and 12, 1954).
- (239) Hammer, E. W., and Peterson, R. E., "Design Specifications for Stainless Steel, Type 301", paper presented at the Philadelphia Regional Technical Meeting of American Iron and Steel Institute (October 6, 1954).
- (240) Weckesser, Louis B., Jr., "Tensile Properties of Alciad 2024-T3 Aluminum at Elevated Temperatures for Short Times", Johns Hopkins University, Applied Physics Laboratory, Section T, Ghi-859 (February, 1956).

(241) "Unitoy 19-9DL and Unitey 19-9DX Heat-Resistant Superalleye", Universal-Cyclops Steel Corporation, Bridgeville and Titusville, Pa.

- (242) Bishop, S. M., Spretnak, J. W., and Fontana, M. G., "Mechanical Properties Including Fatigue of Titanium-Base Alloys, KC-13013 and Ti-150A at Very Low Temperatures", American Society of Metals Transactions, Vol 45, 1953, page 993 +.
- (243) Chow, J. G. Y., and Kaufman, D. W., "Improved Ferritic Steel Can Replace Austenitic Steel", Iron Age, Vol 170, No. 19, November 6, 1952, pages 166-169.
- (244) Data from General Electric Company, Evendale, Cincinnati, Ohio.
- (245) Mote, M. W., Jr., and Frost, P. D., "The Engineering Properties of Commercial Titanium Alloys", Battelle Memoria! Institute TML Report No. 15, September 22, 1955, 18 pages.
- (246) Gohn, C. R., Guerard, J. P., and Freynick, H. S., "The Mechanical Properties of Wrought Phosphor-Brenze Alloys", ASTM Special Technical Publication No. 183 (1956).
- (247) "Republic Titanium and Titanium Alloys", Republic Steel Corporation, Alloy Steel Division, Massillon, Ohio, 1934, 60 pages.
- (248) Turner, H. C., "Titanium Alloy Sheet Stress-Strain Curves for Long Strip Specimens", Consolidated Vultee Aircraft Corporation, Report No. 8340, March 29, 1754, 6 pages.
- (249) Smith, G. V., Roeloffs, R., and Garofalo, F., "Greep Rupture Strength of Bar and Sheet Stock of Austenitic Cr-Ni-Mo Steel at 1100-1500 F", United States Steel Corporation, Kearney, New Jersey, Report No. 750 (August, 1955).
- (250) "Tensile Compressive Bearing and Shear Data for an Mo-6Al-4V Titanium Extrusion at RT 300 F, 500 F, 700 F, and 900 F", Report No. 1445, North American Aviation, Downey, California (March, 1955).

のののでは、「は、これできないのできない。」というないないが、「これないのでは、これのできない。」というないのできない。

- (251) "Bend Compression, Sheet Classification, and Tensile Data &Al-4V and 4Al-4V Tiranium Sheet at RT 700 F and 900 F", Report No. MRR 55-526, North American Aviation, Downey, California (December 6, 1955).
- (252) Hanagan, M. D., McCulloch, A. J., and Pitta, P. R., "Evaluation of the Preparties of RG 130A Tithnium Alley Sheet", Contract No. (a)51-751C, Report No. 8880, Chance Yought Aircraft, Dallas, Texas (March, 1953).
- (253) "Armco 17-7PH Stainless Steel Condition TH-1050, Comparison With Other Structural Materials At Elevated Temperatures", Armco Steel Corporation, Middletown, Ohio (September 26, 1955).

- (254) Smith, R. B., "New Temper Designations for Aluminum Alloys", Reynolds Metals Company, Louisville, Ky.
- (255) Allegheny Ludium Steel Corporation, Pittsburgh, Pa., "Stainless Bars" (1955).
- (256) "Fabrication of U.S.S. Stainless and Heat-Resisting Steels", United States Steel, Pittsburgh 30, Pennsylvania (1952).

- (257) "Welding Brazing and Hot Cutting Republic Enduro Stainless Steels", Republic Steel Company (1952), Massillon, Ohio.
- (258) A Preliminary Report on "The Effect of Cold-Working and Aging on the Hardness and Tensile Properties of Haynes Alloy No. 25 Sheet and Bar", Haynes Stellite Company, Kokomo, Ind. (December, 1951).
- (259) "Ultra High Strength Steels in Aircraft Applications" Symposium SP-120 Seminar Presented at University of California (March 23, 25, and 30, 1953).
- (260) "Crucible Precision Investment Castings", Crucible Steel Company of America, Pittsburgh 30, Pennsylvania (1955).
- (261) "High Alloy Castings", Duraloy Company, Scottdale, Pa. (1955).
- (262) Smith, G. V., and Seens, W. B., "Properties of Hardened 1040, 4340, and Ni-Cr-Mo-V Steels", American Societ: for Testing Materials, Proceedings, Vol 54, January 1954, pages 1028+.
- (263) Smith, C. V., Seens, W. B., Dulis, E. J., Jensen, W. L., and Houston, E. G., "Strength of Two Hardened Alloy Steels in the Temperature Range 75°F to 700°F", Supplement to Report 623, U.S. Steel (January, 1950).
- (264) Smith, G. V., and Seens, W. B., 'Cooperative Study of Strength of 0.2 Per Cent Carbon Steel at Elevated Temperatures", Report No. 704, U. S. Steel Corp., Pittsburgh, Pa. (September, 1952).
- (265) Smith, G. V., Seens, W. B., Dulis, E. J., Jensen, W. L., and Houston, E. G., "Strength of Two Hardened Alloy Steels in Temperature Range 75°F to 700°F", Report No. 623 (U.S. Steel Corp., Pittsburgh, Pa.) (August, 1949).
- (266) Seens, W. B., Smith, G. Y., Dulis, E. J., Jensen, W. L., and Houston, E. G., "Mechanical Tests of Streis for High Speed Airplane Winger, U. S. Steel Corp., Pittsburgh, Pa. Report No. (August, 1947).

- (267) "The Mechanical Properties of Quenched and Tempered Medium-Carbon Alloy Steels", American Iron and Steel Institute (March, 1956).
- (268) Technical Bulletin, The Babcock and Wilcox Company, Beaver Falls, Pennsylvania,
- (267) "Machining and Grinding Titanium", The Cincinnati Milling Machine Company, Cincinnati, Ohio.
- (270) Jenkins, W. D., and Digges, T., "Influence of Prior Strain History on the Tensile Properties and Structure of High Purity Copper", Journal of Research, National Bureau of Standards, Vol 49, No. 3, September 1952, pages 167-186.
- (271) Jenkins, W. D., and Digges, T. G., "The Effect of Temperature on the Tensile Properties of High-Purity Nickel", Journal of Research, National Bureau of Standards, Vol 48, No. 4, April 1952, pages 313-321.
- (272) Jenkins, W. D., and Digges, T. G., "Creep of High-Purity Copper", Journal of Research, National Bureau of Standards, Vol 45, No. 2, August 1950, pages 153-172.
- (273) Jenkins, W. D., Digges, T. G., and Johnson, C. R., "Effect of Temperature on the Tensile Properties of a Commercial and a High-Purity 70 Per Cent Nickel, 30 Per Cent Copper Alloy", Journal of Research, National Bureau of Standards, Vol 54, No. 1, January 1955, pages 21-36.
- (274) Jenkins, W. D., Digges, T. G., and Johnson, C. R., "Creep of High-Purity Nickel", Journal of Research, National Bureau of Standards, Vol. 53, No. 6 (December, 1954).
- (275) Jenkin W. D., Digges, T. G., "Creep of Annealed and Cold-Drawn High-Purity Copper", Journal of Research, National Bureau of Standards, Vol 47, No. 4, October 1947, pages 1129-1140.
- (276) A Handbook of Seamless Steel Tubing, Timken Roller Bearing Company, Canton, Ohio.
- (277) Rochl, E. J., "Mechanical Properties of Nickel Deposits", Monthly Review, Vol 34, October 1947, pages 1129-1140.
- (278) Data from Ampco Metal Inc., Liliwaukee, Wisconsis.
- (214) Data from Superior Tube Co., Norristown, Pa.
- (280) Data from Mueller Brass Co., Port Huron, Mich.

- (292) Ga. Malenock, P. R., and Smith, G. V., "Hardness of Various Steels at Elevated Temperatures", American Society for Metals, Transactions, Vol. 45, 1953, pages 377-396.
- (293) "Hot Hardness Results of Bearing Steel Compositions", Unpublished, U. S. Steel Corp., Pittsburgh, Pa.
- (294) "Elastic Moduli and Poisson's Ratio of Stainless "W" at Room and Elevated Temperatures", United States Steel Co., Pittsburgh, ra.
- (295) Smith, G. V., and Seens, W. B., "Short-Time Tension and Creep-Rupture Properties of Hardened 1040, 4340, and Ni-Cr-Mo-V Steels Up to 1000 F", American Society for Testing Meserials, Proceedings, Vol 54, 1954, page 1028 +.
- (296) Smith, G. V., Seens, W. B., and Dulis, E. J., "Hardened Alloy Steel for Service Up to 700 F", American Society for Testing Materials, Proceedings, Vol 50, 1950, pages 882-894.
- (297) "Elevated Temperature Tensile Properties of Type 321 Stainless Steel" (A) Load-Slongation Curves for Above, U. S. Steel Corp., Pittsburgh, Pa.
- (298) "Elevated Temperature Tensile Properties of Type 347 Stainless Steel", (a) Load-Elongatio. Curves for Above, U. S. Steel Corp., Putsburgh, Pa.
- (299) "Elevated Temperature Tensile Properties of Type 302/304 Stainless Steel", (a) Load-Elongation Curves for Above.
- (300) "Elevated Temperature Tensile Properties of 0.5 Per Cent Mo Steel".
- (301) Original Data From the Files of Dow Laboratories, Dow Chemical Company, Midland, Michigan.
- (302) "Development of Magnesium Alloys for Elevated Temperature", Unpublished data, Battelle Memorial Institute, Wright Field Contract No. W33-038 ac-7202.
- (303) "Metal Progress Data Sheets 1 Through 192", 1954, American Society of Metals, Cleveland, Ohio.
- (304) National Bureau of Standards, "Mechanical Properties of Metals and Alloys", Circular C-447 (December 1, 1954).
- (305) "Designing With Magassium", American Magnesium Corporation. Subsidiary of Aluminum Company of ...nerica, Pittsburgh, Pa. (1947, 1956).

- (281) Koffler, R. W., Pennington, W. J., and Richmond, R. M., "Elevated Temperature Properties of Some Vacuum-Melted Super Alloys", Report to the NACA Subcommittee on Power-Plant Materials (March 5, 1956).
- (282) Carney, D. J., "High Nitrogen Steels: New Stainless Family", Steel, Vol 137, No. 19, November 7, 1955, pages 138-144.
- (283) Smith and Wetmore, "Tensile Properties of Metals Heated at Elevated Rates", NAVORD-1178, ATI 72343.
- (284) Simmons, W. F., VanEcho, J. A., and Cross, H. C., Battelle Memorial Institute, "Short-Time, High-Temperature Properties of Heat Resisting Alloy Sheet", Rand Report R-147, Rand Corporation (June, 1949).
- (285) "Creep-Rupture Strength of an Extrusion-Press Liner Steel at 1000 F", ARL Project No. 44.12-007 (1), (March 14, 1956). U. S. Steel Corp., Monroeville, Pa.
- (286) "Pipe and Tubes for Elevated-Temperature Service", National Tube Co., Pittsburgh, Pa., Bulletin No. 26.
- (287) Smith, G. V., and Dulis, E. J., "Effect of Manufacturing Practice on Creep and Creep-Rupture Strength of Low-Carbor Steel", American Society for Testing Materials, Proceedings, Vol 49, 1949, pages 584-601.
- (288) Dulis, E. J., Smith, G. V., and Houston, E. G., "Creep and Rupture of Chromium-Nickel Austenitic Stainless Steels", American Society of Metals, Vol 42, 1950, pages 935-980.
- (289) Smith, C. V., Dulis, E. J., and Houston, E. G., "Creep and Rupture of Several Chromium-Nickel Austenitic Stainless Steels", American Society of Metals, Vol 45, Pt. II, 1953, pages 42-76.
- (290) Garofalo, F., and Smith, G. V., "The Effect of Time and Temperature on Various Mechanical Properties During Strain Aging of Normalized Low-Carbon Steels", American Society for Metals, Transactions, Vol 47, Report No. 550, 1955, pages 957-983.
- (291) Garofalo, F., Malenock, P. R., and Smith, G. V., "The influence of Temperature on the Elastic Constants of Some Commercial Steels", American Society for Testing Materials, Special Publication No. 129, 1952, pages 10-30.

- (306) Rosenberg, S. J., "Effect of Low Temperatures on the Properties of Aircraft Metals", Journal of Research of the National Bureau of Standards, Vol 25, December 1940, pages 673-701.
- (307) Funtana, M. G., "Mechanical Properties and Physical Metallingy of Aircraft Alloys at Very Low Temperatures", Interim Report, Results of impact and Hardness Tests, Contract No. 533-acc15698 (16915) (September 15, 1947).
- (308) American Society for Testing Materials, ASTM Standards, Part 1-B (1946, 1947).
- (309) "Data Book" (1943, 1948), American Magnesium Corporation, Subsidiary of Aluminum Company of America, Pittsburgh, Pa.
- (310) "Dow Meial Data Book" (1944), Don Chemical Company, Midland, Michigan,
- (311) The Producers, Suppliers, and Menufacturers of Elektron Magnesium Alloys, "Elektron Magnesium Alloys" (1947), The Kynoch Press, Birmingham, England.
- (312) Wyman, L. L., "High Temperature Properties of Light Alloys Part 2 Magnesium", OSRD Report No. 4159, M292 (September 18, 1944).
- (313) Dorn, J. E., and Thomsen, E., "Magnesium-Notes on the Modutes of Elasticity", Light Metal Age, Vol 1, No. 2, July 1943, pages 11, 24-25.
- (314) Craighead, C. M., Eastwood, L. W., and Lorig, C. H., "An Appraisal of the Usefulness of Aluminum Alloys for Supersonic Aircraft and Guided Missiles", Battelle Memorial Institute, Report to Project RAND (August 2, 1948).
- (315) Templin, R. L., and Paul, D. A., "Mechanical Properties of Aluminum and Magnesium Alloys at Elevated Temperatures", ASTM-ASME Symposium on Effect of Temperature on Metals, pp 290-315 (1931).
- (316) Jackson, L. R., Grover, H. J., and McMaster, R. C., "Advisory Report on Fatigue Properties of Aircraft Mate. als and Structures", War Metallurgy Committee, OSRD No. 6600, Serial No. M-653 (March 1, 1946).
- (317) Found, G. H., "The Notch Sensitivity in Fatigue Loading of Some Magnesium-Base and Aluminum-Base Alloys", American Society for Testing Materials, Proceedings, Vol 46, 1946, pages 715-740.

- (318) Moore, A. A., and McDonald, J. C., "Tensile and Greep Strengths of Some Magnesium-Base Alloys at Elevated Temperatures", American Society for Testing Materials, Proceedings, Vol 46, 1946, pages 970-989.
- (319) MacDonald, John C., "Tensile, Creep, and Fatigue Properties at Elevated Temperatures of Some Magnesium-Base Alloys", ASTM Proceedings, Vol 43, pp 737-754 (1948).
- (320) Battelle Memorial Institute, "Magnesium-Cerium Forging Alloys", Umublished data, NACA Contract No. NAw-5383 and No. NAw-5627.
- (321) Battelle Memorial Institute, "Development of Magnesium-Cerium Alloys for Elevated-Temperature Service", Unpublished data, Navy Department Contract No. NOa(s) 8957.
- (322) Leonis, T. E., and Murphy, J. P., "The Properties of Cerium Containing Alloys at Room and Elevated Temperatures", Metals Technology, Technical Publication 1995 (April, 1946).
- (323) Jackson, L. R., and Grover, H. J., "The Fatigue Strength of Some Magnesium Sheet Alloys", American Society for Testing Materials, Special Technical Publication No. 1995, Vol 46, 1946, pages 783 +.
- (324) Ar.ny-Navy-Civil Committee on Aircraft Design Criteria, ANC Bulietin "Strength of Aircraft Elements", Aeronautical Board,

ANC-5 Amendment 1 ANC-5 Amendment 2 December, 1942 October 22, 1943 August, 1946

- (325) Craighead, C. M., Williams, R. D., and Voldrich, C. B., "Survey on Welding Aluminum and Magnesium", Battelle Memorial Institute Peport to Office of the Chief of Ordnance, War Department, PB78712, January 3, 1947. (OTS Mimeograph, \$8.00).
- (326) Air Technical Service Command, "Magnesium Alloys Properties and Aircraft Applications", AAF Technical Report 5156 (October 17, 1944).
- (327) Army Air Forces, "Investigation of Stress Corrosice".

Part I Test Methods and Progress
Part II Results of Test and Conclusions

AAF Technical Report 5144 (September 21, 1944, and October 16, 1946).

(328) Hunter, M. A., "Progress Reports on the Physical and Stress Corrosion Properties of Magnesium Alloy Sheet", War Metallurgy Committee.

M152	November, 1943
M197	January, 1944
M237	April, 1944
M471	March, 1945

- (329) Loose, W. S.: Memorandum on "Corresion Resistance of Magnesium in Various Chemicals", Dow Chemical Company, Midland, Mich. (September 26, 1947).
- (330) Murphy: A. J., and Payne, R. J. M., "Magnesium-Cerium-Zirconium Alloys: Properties at Elevated Temperatures", Journal of Institute of Metals, Vol 73, 1946, pages 105-127.
- (331) Leontis, T. E., "The Room and Elevated Temperatures Properties of Some Sand Cast Magnesium-Base Alloys Containing Zinc", Metals Technology, 7. P. 2371, June 1948, (individually paged), 35 pages.
- (332) Metals Handbook Supplement, American Society for Metals, Cleveland (August 15, 1955).
- (333) "The Properties of Binary and Polynary Magnesium Alloys Containing Cerium at Room and Elevated Temperatures", Report No. 13732, Dow Chemical Company, Midland, Michigan.
- (334) Dineen, D. E., and Berson, N. D., "Cast and Extruded Magnesium Alloys Some Mechanical Tests at Room and Low Temperatures", Meial Industry, Vol 71, August 8, 1947, pages 103-105.
- (335) Zambrow, J. L., and Fontana, M. G., "Mechanical Properties, Including Fatigue of Aircraft Alloys at Very Low Temperatures", ASM, Preprint No. 19 (1948).
- (336) Eastman, E. J., McDonald, J. C., and Moore, A. A., "The Relation of Stress to Strain in Magnesium-Base Alloys", Journal of the Aeronautical Sciences, Vol 12, pp 273-280 (July, 1945).
- (337) Rappleyea, F. A., Porry, R. E., and Ansel, G., "Influence of Prestressing and Cyclic Stressing on Stress-Strain Characteristics of Magnesium Alloys", Journal of the Aeronautical Sciences, Vol. 12, pp 447-454, and 460 (October, 1945).

(338) Found, George H., "Fatigue Characteristics of Magnesium Castings", ASTM Symposium on Testing of Parts and Assemblies, Technical Publication No. 72 (1946).

- (339) Found, G. H., "Magnesium Alloy Castings Relative Significance of Design and Mechanical Factors of Serviceability", American Foundryman, Vol 9, No. 6, June 1946, pages 43-49.
- (340) Found, George H., "Relation of Design and Mechanical Tactors to the Serviceability of Magnesium Castings", paper to be presented before the Affiliate Council of the Engineering Society of Detroit.
- (3(1) "Results of Tensile Test of Magnesium Alloys at Low Temperatures", M. T. No. 022546-J, Aluminum Research Laboratories, Fittsburgh, Pa. (May 29, 1947).
- (342) Fisher, E. F., "Room-Temperature Mechanical Properties of Magnesium Allo, Sheet After Heating at Elevated Temperatures", American Magnesium Corporation, Subsidiary of Aluminum Company of America, Pittsburgh, Pa., Metallurgical Department Report (January 17, 1949).
- (343) Johnson, H. A., "Experimental Magnesium Alloys Part 3 T ermal and Electrical Properties of Magnesium Base Alloys", WADC Technical Report 54-83, Part 3, 1954.
- (344) Blathenwish, A. A., and Lazan, B. J., "Fatigue Properties of Extruded Magnesium Alloy 2K60 Under Various Combinations of Alternating and Mean Asia: Stress", WADC Technical Report 53-181.
- (345) Johnson, H. A., "Experimental Magnesium Alloys Part 4 Evaluation of HK31", WAINC Technical Report 54-83, Part 4 (1954).
- (346) Elevated Temperature Iensile Properties of Type 316 Stainless Steel
  (a) Load-Elongation Curves, U. S. Steel Corp., Pittsburgh, Pa.
- (347) Elevated Temperature Tensile Properties of Type 302 Stainless Steel (a) Load-Elongation Curves, U. S. Steel Corp., Pittsburgh, Pa.
- (348) Elevated Temperature Tensile Properties of Type 8Cr-1Mo Stainless Steel (a) Load-Elongation Curves for Above, U. S. Steel Corp, Pittsburgh, Pa.
- (349) Load Elongation Diagram of 422 Medified Stainless Steel (USS), Unpublished data,
- (350) Welcze Lasearch supplement (May, 1984).

ション・ション・自己のころのころの意味がなるのでは、

- (351) Technical Information on Jalloy the Mining Steel, from Jones and Laughlin Steel Corp., Pittsburgh, Pa., 12 pages.
- (352) Miller, D. E., "Determination of the Physical Properties of Ferrous and Nonferrous Structural Sheet Materia's at Elevated Temperatures", Part 4, Armour Research Foundation of Illinois Institute of Technology (December, 1954).
- (353) McDonnell Aircraft Corporation, St. Louis, Mo., 1954 with some 1955 revisions, Report No. 3697.
- (354) "Nickel and High-Nickel Alloys for Pressure Vessels", by Wilson, R. M., Jr., and Burchfield, W. F., No. 24 (January, 1956), Welding Research Council Bulletin Series.
- (355) Rey, W. K., NACA Research Memorandum, "Elevated Temperature Properties of Two Titanium Alloys" (April 24, 1956).
- (356) Miller, D. E., AF-TR-6517-Part 4, "RC-130A, Titanium Alloy" (December, 1954).
- (357) Fairbairn, Gordon, "North American Aviation, Inc., "Expands Use of Titanium to Airframes", Journal of Metals, Vol 7, No. 3 (March, 1955), pp 449-452.
- (358) Roach, D. B., and Hall, A. M., "The Engineering Properties of Precipitation-Hardenable Stainless Steels", TML Report 48 (July 20, 1956).
- (359) See American Iron and Steel Institute, New York, Unpublished data,
- (360) Lula, R. A., "Cold Worked 301 Stainless Still Strong at 800 F", Materials and Methods, Vol 44, No. 3 (September, 1955), pp 100-102.
- (361) Hughers. Philip J., Inge, John E., and Prosser, Stanley B., "Tensile and Co. prossive Stress-Strain Properties of Some High-Strength Sheet Alloys at Elevated Temperatures", National Advisory Committee tor Aeronautics Technical Note 3315, Langley Aeronautical Laboratory, Langley Field, Va., Washington (November, 1954).
- (362) Trapp, W. J., "Elevated Temperature Fatigue Properties of SAE 4340 Steel", WADC Technical Report 52-325, Part 1, December 1952, 11 pages.
- (363) Sachs, George (Syracuse University), "Survey of Low-Alloy Aircraft Steels Heat Treated to High-Strength Levels", WADC Technical Report 53-254, Part 4, 1953.

## Copy available to DTIC does not permit fully legible reproduction

- (2.1) Preliminary Data HK-31, Brooks and Perkin , Inc., Letroit, Michegan, New Magnesium Thoriam Alloy.
- (303 PHK-31-XA Magnesium Alloy Sheet and Plane, (Interim Data)<sup>m</sup>, The Dow Chemical Company, Midland, Michigan (February 16, 1956).
- (366) Smith, G. V., Seens, W. B., and Dulis, E. J., "Plandened Alloy Steria for Service Up to 700 F", American Society for Testing Materials, "rocceedings, Vol 50, 1950, page 882 +.
- (367) Layward, D. C., "Mechanical Properties of RC 130A Sheet Estanium at Room and Elevated Temper Aures", Anval Aircraft Establishment, Tech. Note Met. 214, (November, 1955).
- (268) Douglas Aircraft Company, Inc., Sant: Monica Testing, "Survey of a Resisting Materials", Report No. Dou-2056, p. 12-13.